

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Kalamazoo

(County)

Located in:

Corner Code #

Charleston Section 8

1. Public Land Survey

T 2 S R 9 W

D-3

2. Property Controlling  
in Section

S

T

R

W

3. Miscellaneous

S

T

R

W

Property in Sec.

S

T

R

W

4. Lot No. , Recorded Plat

5. Private Claims

I, Robert E. Snell in a field survey on January 12, 19 94,

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by U. S. Government Survey in 1825. Set Post.

Wh. Oak 12" South 69°-W 41 Lks (27.06')

Wh. Oak 18" South 33°-E 57 Lks (37.62')

1872-S. Hodgeman County Surveyor-set stone from stump of one witness and roots of other.

Y. Oak 5" South 86°-W 26½ Lks (17.49')

1883-F. Hodgeman County Surveyor-ran North 69°-E 41 Lks from stump of U.S. bearing tree

to stone of resurvey. Bored 3', put one foot earthen post, one foot of stone, and one foot earthen post on top with stone around.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: Y. Oak 6" North 05°-W 41 Lks (27.06')  
Y. Oak 7" N 75°-W 23½ Lks (15.51')

Found solid clay tile with stone around.

**RATIFIED  
BY KALAMAZOO COUNTY  
REMONUMENTATION  
PEER GROUP**  
1-20-94

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-3 North 1/4 post Section 8, T. 2 S., R. 9 W., ratified by Kalamazoo County Remonumentation Program Peer Group on January 20, 1994. Found solid clay tile with stone around as called for in remonumentation survey in 1883 by F. Hodgeman and is accepted as a careful and faithful perpetuation of the position of the original corner. Placed remonumentation sleeve over solid clay tile.

PK Nail in N side 30" Oak West 13.14'  
PK Nail in NE side 14" Hickory N 35°-W 30.49'  
PK Nail in W side 24" Hickory N 15°-E 4.63'  
PK Nail in W side 12" Oak S 25°-E 11.75'

Fence to North East 6.6'  
R.R. Tie  
Fence Cor. S 30°-E 17.2'

Signed by

Robert E. Snell

Date

3-15-94

Surveyor's Michigan License No.

9734