

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

LIBER

1 1464

For corners in

Kalamazoo

(County)

Located In:

Corner Code #

Kalamazoo Twp.

1. Public Land Survey

T 2 S. R 11 W.

E-12

2. Property Controlling  
in Section

S T R

3. Miscellaneous

S T R

Property in Section

S T R

4. Lot No. , Recorded Plat

5. Private Claims

Register of Deeds Stamp & File Number

I, Robert E. Snell, in a field survey on February 16, 19 96

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE:** Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1827: United States Government Surveyors; set 1/4 Section post.

W. Oak 10" S. 59° E. 4 lks.  
W. Oak 9" S. 31° W. 27 lks.

1885: F. Hodgman, County Surveyor; found stake standing Northwest 6 lks. from U.S. bearing tree. Set post.

Wh. Oak 16" S. 25° E. 43 lks.  
Wh. Oak 5" S. 88° E. 52 lks.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1940: Wilkins & Wheaton Engineering Co.; found tile.

15" R. Oak S. 12° E. 39.35' 10" Hickory S. 50° E. 43.95'\*  
15" R. Oak S. 75° E. 51.58' 12" Oak N. 25° E. 21.00'\*  
12" Hickory S. 85° E. 45.72' 14" W. Cherry N. 05° E. 30.13'\*

1996: Found 3" round tile with "x" on top from 3 of above witnesses. Tile is 6" below surface along South side of chain link fence corner, base fence corner is 0.5' North and 0.35' East of tile.

\* Denotes witnesses found in 1940 & 1996.

**RATIFIED  
BY KALAMAZOO COUNTY  
REMONUMENTATION  
PEER GROUP**

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-12: East 1/4 post, Section 32, T. 2 S., R. 11 W., Ratified by the Kalamazoo County Remonumentation Program Peer Group on March 21, 1996 and is accepted as a careful and faithful perpetuation of the position of the original corner. Found 3" round tile with "x" on top as set by F. Hodgman in an 1885 Remonumentation survey. Placed sleeve over tile.

PK Nail in Southeast Side 34" W. Cherry N. 14° E. 30.41'\*  
PK Nail in Southeast Side 18" Oak N. 48° E. 21.42'\*  
PK Nail in North Side 20" Hickory S. 32° E. 44.03'\*  
PK Nail in Southeast Side 22" W. Cherry S. 76° W. 5.39'

Signed by

Robert E. Snell

Date

3-25-96

Surveyor's Michigan License No.

9734