

SURVEY &  
REMONUMENTATION

2 - MAY 28 1997

COMMISSION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Kalamazoo

Located In:

Corner Code #

Kalamazoo Twp.

1. Public Land Survey

T 2S R 11W

M-04

2. Property Controlling  
in Section

S  
S

T  
T

3. Miscellaneous  
Property in Sec.

S  
S

T  
T

4. Lot No. . Recorded Plat  
5. Private Claims

I, Robert E. Snell, in a field survey on Jan. 4, 19 96 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1825: United States Government Surveyors; set 1/4 Section post.

W. Oak 10" S. 71 $\frac{1}{2}$ <sup>0</sup> W. 52 lks.  
W. Oak 18" N. 22<sup>0</sup> W. 24 lks.

1885: F. Hodgman, County Surveyor; found stake correct, stumps of both U.S. bearing trees standing. Set post.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1909: Glen C. Wheaton, Michigan Engineering Co.; East 1/4 post tile.

W. Oak N. 60<sup>0</sup> E. 2 lks. (Baker's Subdivision)

1920: Glen C. Wheaton, Michigan Engineering Co.; found tile (Plat of Washburn Acres).

W. Oak 15" S. 30<sup>0</sup> W. 29.25'  
R. Oak 20" S. 35<sup>0</sup> E. 27.50'  
R. Oak 18" N. 50<sup>0</sup> W. 45.50'

1996: Found 3" round tile with "x" on top at surface of ground.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-04: East 1/4 post, Section 12, T. 2 S., R. 11 W., ratified by the Kalamazoo County Remonumentation Program Peer Group on January 18, 1996 and is accepted as a careful and faithful perpetuation of the position of the original corner. Found 3" round tile with "x" on top as set by F. Hodgman in a 1885 remonumentation survey. Placed a remonumentation sleeve over tile.

PK Nail in West side 18" Oak S. 04<sup>0</sup> E. 29.74'  
Nail/Tab in Southwest side 10" Oak N. 50<sup>0</sup> W. 7.05'  
(MSHD) Nail/Tab in South side 32" Oak N. 64<sup>0</sup> W. 30.62'  
(MSHD) Nail/Tab in East side 12" Oak N. 10<sup>0</sup> W. 4.37'  
(MSHD) PK Nail in West side 26" Oak North 21.96'

Signed by Robert E. Snell  
Surveyor's Michigan License No. 9734

Date 10-14-96

STATE OF MICHIGAN  
COUNTY OF KALAMAZOO  
RECORDS & CLERK  
96 OCT 18 AM 11 32  
CLERK-REGISTRAR

LIBER 2PAGE 066

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6			5		4		3		2		1	
3													
4	7			8		9		10		11		12	
5													
6	18			17		16		15		14		13	
7													
8	19			20		21		22		23		24	
9													
10	30			29		28		27		26		25	
11													
12	31			32		33		34		35		36	
13													

RATIFIED  
BY KALAMAZOO COUNTY  
REMONUMENTATION  
PEER GROUP  
1-18-1996