

MAY 16 1996

**COMMISSION**

**LAND CORNER RECORDATION CERTIFICATE**  
Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN  
COUNTY OF KALAMAZOO  
RECEIVED FOR RECORD

'96 MAR 13 PM 3 42

For corners in  
Kalamazoo  
(County)  
Pavilion Twp.

Located In:

Corner Code #

*James P. Gange*  
CLERK-REGISTER

- |                                    |   |   |    |   |    |    |      |
|------------------------------------|---|---|----|---|----|----|------|
| 1. Public Land Survey              | T | 3 | S. | R | 10 | W. | G-05 |
|                                    | T |   |    | R |    |    |      |
|                                    | T |   |    | R |    |    |      |
|                                    | T |   |    | R |    |    |      |
| 2. Property Controlling in Section | S |   | T  |   | R  |    |      |
|                                    | S |   | T  |   | R  |    |      |
| 3. Miscellaneous                   | S |   | T  |   | R  |    |      |
| Property in Section                | S |   | T  |   | R  |    |      |

LIBER

**1 1451**

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, Robert E. Snell, in a field survey on January 24, 19 96, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE:** Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

**A. Description of original monument and accessories and/or subsequent restoration:**

1826: Original United States Government Surveyors; set post, corner to Sections 9, 10, 15 and 16.

W. Oak 14" N. 46° E. 89 lks.  
W. Oak 12" S. 05° W. 16½ lks.

1888: F. Hodgman, County Surveyor; found iron shaft and stones and pine bearing tree standing. Set post.

**B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:**

1996: Found 3" round tile with "x" on top in a pile of rocks just below the surface of the ground.

**RATIFIED**  
**BY KALAMAZOO COUNTY**  
**REMONUMENTATION**  
**PEER GROUP**  
2-15-96

**C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:**

G-05: Southeast corner Section 9, T. 3 S., R. 10 W., ratified by the Kalamazoo County Remonumentation Program Peer Group on February 15, 1996 and is accepted as a careful and faithful perpetuation of the position of the original corner. Found 3" round tile with "x" on top as set by F. Hodgman, County Surveyor in 1888 in a remonumentation survey. Tile is in a pile of stones just below surface of ground. Placed a remonumentation sleeve over tile.

PK Nail in North side	14" W. Cherry	S. 80° W.	41.71'
PK Nail in North side	14" W. Cherry	West	63.46'
PK Nail in West side	Power Pole	N. 15° E.	21.30'
Line of Power Poles		East	4.80'

Signed by

*Robert E. Snell*

Date

3-12-96

Surveyor's Michigan License No. 9734

