

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF-- LOCATED IN-- CORNER CODE NUMBER

1. PUBLIC LAND SURVEY T. 3 S., R. 11 W. A5, A6, A7, B5, B6, C5

2. PROPERTY CONTROLLING IN SECTION T. N. S., R. E. W.

3. MISCELLANEOUS PROPERTY IN SECTION T. N. S., R. E. W.

4. LOT NO. , RECORDED PLAT

5. PRIVATE CLAIMS

STATE OF MICHIGAN
COUNTY OF KALAMAZOO
RECEIVED FOR RECORD
JUN 5 3 06 PM '76
REGISTER OF DEEDS
REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, ALLEN H. McMACHEN do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on DEC. 1975, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on 19 , found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

A5-NW COR
FD. IRON

A7-SE. COR
FD. IRON IN
MON. BOX

B6 CEN.
SET AT INTERSECTION
OF QUARTER LINES

A6-W 1/4
FD. IRON

B5-N 1/4
FD IRON IN
MON. BOX

C5 NE. COR
FD PIPE IN
MON. BOX

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-5 NW. COR
IRON ROD

26" OAK N 30° E. 72.12
15" PINE S 25° E. 54.79
30" OAK S. 50° W. 40.06

A7-SE. COR.
IR. IN MON. BOX

U.P. N 20° W. 78.53
6" OAK S. 40° E. 62.62
IRON ROD EAST 33.0'

B6 CEN.

CONC. MON.
15" OAK S 80° E. 58.21'
24" OAK S 45° W. 19.67'
15" OAK SOUTH 37.47'

A-6 W 1/4

IRON ROD
24" OAK S 80° W 25.00'
CONC. MON. EAST 33.0'
24" OAK S 54° E. 43.25'

B-5 N 1/4

IR. IN. MON. BOX
FENCE LINE TO SOUTH
26" OAK S. 65° W. 55.73'
24" OAK N. 5° E. 33.17'

C5 NE COR.

PIPE IN MON. BOX
18" WAL. N. 10° E. 37.72'
12" WAL. S. 45° E. 56.25'

SIGNED BY

Allen H. McMachen

DATE

12/23/75

SURVEYOR'S MICHIGAN REGISTRATION NO.

16935

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY

CHIEF OF SURVEY PARTY

DATE

APPROVED AND SIGNED BY

MICHIGAN REGISTERED LAND SURVEYOR

