

SURVEY & REMONUMENTATION

FEB 08 2000

LIDER

2PAGE 449

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Kalamazoo
(County)

Located In:

Corner Code #

1. Public Land Survey

T 3S R 12W

D-1

2. Property Controlling
in Section

S

T R

3. Miscellaneous

S

T R

Property in Sec.

S

T R

4. Lot No. , Recorded Plat

5. Private Claims

I, Thomas W. Chettleburgh, in a field survey on May 27, 19 97
do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points
mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as
required in the current manual of survey instructions of the United States Department of the Interior,
Bureau of Land Management or by a decree of a Court of Law and for that the corner points
mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of
Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented,
recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
Holtgerman, 1870, set stake in marsh 73 1/2 links east of S 1/4 Corner Section 32
Al McMachen, 1987, set iron bar in marsh on bi-section of North line Section 48.5'
East of S 1/4 Corner Section 32

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
1997, Found iron bar in marsh 48.51' East of S 1/4 Corner Section 32 on Township line
The iron bar was ratified by the Kalamazoo County Remonumentation Program Peer Group
on July 16, 1997.

This position not established by original government surveyors. This monument is accepted
as the best available evidence of the position of the corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Replaced iron bar with 30" Harrison Monument

Spike E side	13" Oak	S10°W	70.65'
Spike SE side	33" Oak	S82°W	57.40'
Harrison Monument (S1/4 Cor Sec. 32)	West		48.51'
Spike E side	13" Maple	N40°W	59.40'

RATIFIED
BY KALAMAZOO COUNTY
REMONUMENTATION
PEER GROUP
7-16-1997



Signed by

Thomas W. Chettleburgh

Date January 21, 1999

Surveyor's Michigan License No.

16036