

FEB 08 1999

SECTION

**LAND CORNER RECORDATION CERTIFICATE**  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in Texas Twp.

Kalamazoo  
(County)

Located In:

Corner Code #

1. Public Land Survey

T 3S R 12W

F-04

2. Property Controlling  
in Section

S

T R

3. Miscellaneous  
Property in Sec.

S

T R

4. Lot No. , Recorded Plat

5. Private Claims

I, Robert E. Snell, in a field survey on May 4, 19 98 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

This position not established by original government surveyors.

1869: F. Hodgman, County Surveyor; "Set a stake on the East and West 1/4 line midway between the 1/4 post (East and West). W. Oak 6" N. 29° E. 1.06 ch. 40.29 ch. between C 1/4 and E 1/4, C 1/4 and W 1/4. R. Oak 3" S. 62° E. .79 ch.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1998: Found 3/4"x30" iron at the surface. Dug with backhoe to 4' to reach original grade, in the process found large 2'x1'x1' stone with "x" on top 3.42' East of surface iron.

**RATIFIED**  
**BY KALAMAZOO COUNTY**  
**REMONUMENTATION**  
**PEER GROUP**  
5-21-1998

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

F-04: Center of Section 9, T. 3 S., R. 12 W., ratified by the Kalamazoo County Remonumentation Program Peer Group on May 21, 1997 and is accepted as the best available evidence of the position of the corner. Found large (2'x1'x1') stone with "x" on top four feet below the surface believed to have been set in place of stake set in 1865 by F. Hodgman, County Surveyor. Placed 30" Harrison monument over stone in monument box.

PK Nail (over exist. nail) in West Side  
PK Nail (over exist. nail) in East Side  
PK Nail (over exist. nail) in West Side  
Nail/Red Traverse Cap (W&W) on top

Cherry N. 02° W. 53.92'  
Cherry S. 30° E. 36.58'  
Cherry S. 30° W. 35.45'  
Fence Corner N. 10° W. 28.15'

Signed by Robert E. Snell  
Surveyor's Michigan License No. 9734

Date 12-29-98

STATE OF MICHIGAN  
COUNTY OF KALAMAZOO  
RECEIVED FOR RECORD  
98 DEC 29 AM 11 26  
CLERK - REGISTER  
Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6			5		4			3		2		1
3													
4	7			8		9			10		11		12
5													
6	18			17		16			15		14		13
7													
8	19			20		21			22		23		24
9													
10	30			29		28			27		26		25
11													
12	31			32		33			34		35		36
13													