

SURVEY &
REMONUMENTATION

7-
3-
FEB 18 1994

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Kalamazoo

(County)

Located In:

Corner Code #

1. Public Land Survey

T 3 S R 12 W

J-1

2. Property Controlling
in Section

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

LIBER

1 PC1095

CLERK-REGISTER

STATE OF MICHIGAN
COUNTY OF KALAMAZOO
RECEIVED FOR RECORD
94 JUN 21 PM 3 40

Register of Deeds Stamp & File Number

I, Robert E. Snell, in a field survey on December 9, 19 93

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by U.S. Government Survey 1827
1962-Found iron in monument box-Wilkins & Wheaton Engr. Co.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found PK Nail - The original corner and all subsequent evidence was removed in 1992 during sewer construction. The PK Nail in new pavement was placed in 1993 by Wilkins & Wheaton Engr. Co., location of which was established from previous Wilkins & Wheaton Engr. Co. surveys of 1962, 1968, 1971 and 1990.

**RATIFIED
BY KALAMAZOO COUNTY
REMONUMENTATION
PEER GROUP
12-16-93**

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

J-1 North 1/4 post Section 2, T. 3 S., R. 12 W., Ratified by Kalamazoo County Remonumentation Program Peer Group on December 16, 1993. Found PK Nail, removed nail and placed 30" Harrison Monument and Monument Box over monument.

Back of curb at end of curb S 21° E 22.55'

Back of curb at end of curb N 31° E 22.89'

NE cor. conc. telephone pad S 34° W 56.21'

S 1/4 post Section 35, T. 2 S., R. 12 W. Harrison Monument in Monument Box W 81.18'

Signed by

Date

Surveyor's Michigan License No.

9734