

SURVEY & REMONUMENTATION

1 SEP 14 1998

SECTION

For corners in Schoolcraft Twp.

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

Kalamazoo

(County)

Located In:

Corner Code #

1. Public Land Survey

T 4S R 11W

H-05

2. Property Controlling  
in Section

S

T R

3. Miscellaneous  
Property in Sec.

S

T R

S

T R

LIBER

2 PAGE

316

1998 SEP 3 PM 3 26

STATE OF MICHIGAN  
COUNTY OF KALAMAZOO  
RECEIVED FOR RECORD

CLERK - REGISTER

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, Robert E. Snell, in a field survey on May 5, 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

1826: United States Government Surveyors; set 1/4 post in prairie and raised mound.

1889: F. Hodgman, County Surveyor; "Lost, bisected the mile between Section corners and set post."

Southeast corner House

N. 25° E.

149 lks.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1998: Found 3" round tile with "x" on top 1.5' below surface with large stone along North edge of tile. Noted iron rod 2.4 ft. East and 11.0 ft. South of tile.

RATIFIED  
BY KALAMAZOO COUNTY  
REMONUMENTATION  
PEER GROUP  
5-21-1998

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H-05: South 1/4 post, Section 10, T. 4 S., R. 11 W., ratified on May 21, 1998 by the Kalamazoo County Remonumentation Program Peer Group and is accepted as a careful and faithful perpetuation of the position of the original corner. Found 3" round tile with "x" on top, 1.5 ft. below surface of the road. Tile was set by F. Hodgman, County Surveyor, in 1889 Remonumentation survey. Placed Remonumentation sleeve over tile and 18" Harrison monument over in a monument box.

1/2"x18" Iron (Red Cap)	North Edge of Pavement	N. 45° E.	10.74'
1/2"x18" Iron (Red Cap)	South Edge of Pavement	S. 45° E.	19.31'
1/2"x18" Iron (Red Cap)	South Edge of Pavement	S. 45° W.	16.36'
1/2"x18" Iron (Red Cap)	North Edge of Pavement	N. 45° W.	12.82'

Signed by Robert E. Snell

Date 9-2-98

Surveyor's Michigan License No. 9734