

SURVEY & REMONUMENTATION

APR 27 1995

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Kalamazoo

(County)

Schoolcraft Township

Located In:

Corner Code ##

1. Public Land Survey

T 4 S R 11 W

L-11

2. Property Controlling
in Section

S

T

R

3. Miscellaneous

S

T

R

Property in Sec.

S

T

R

4. Lot No. , Recorded Plat

5. Private Claims

I, Robert E. Snell, in a field survey on May 18, 19 94

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1826: U.S. Government Survey; Set 1/4 Section Post.

W. Oak	14"	South	68°	West	34 Lks
W. Oak	13"	North	33°	East	9 Lks

1899: F. Hodgman, County Surveyor; Found stake and stone in line with fence South and 47 2/3 Lks North of new hedge. Set Post. No trees near.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1994: Found a 6" piece of broken tile in monument box. Found a 2' length of 3" diameter tile below.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L-11 South 1/4 Post Section 25, T. 4 S., R. 11 W., Ratified by the Kalamazoo County Remonumentation Program Peer Group on July 21, 1994. Found tile as called for in 1899 remonumentation survey by F. Hodgman and is accepted as a careful and faithful perpetuation of the position of the original corner. Lowered 2' length of tile (badly deteriorated) and placed 20" Harrison monument with monument box over.

PK Nail in West Side	11" Walnut	South	08°	West	84.10'
PK Nail in Northwest Side	Lombardi Popular	North	52°	East	51.66'
PK Nail in North Side	10" Elm	South	65°	West	53.31'
PK Nail in Northeast Side	22" Honey Locust	North	32°	West	78.65'
Center Line "Y" Avenue		South			6.0'

Signed by

Robert E. Snell

Date

12/28/94

Surveyor's Michigan License No.

9734

STATE OF MICHIGAN
COUNTY OF KALAMAZOO
RECEIVED FOR RECORD
94 DEC 30 AM 9 18
CLERK-REGISTER
LIBER
1 PG 1240

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

RATIFIED
BY KALAMAZOO COUNTY
REMONUMENTATION
PEER GROUP
7-21-94