

APR 6 1 1996

COMMISSION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN  
COUNTY OF KALAMAZOO  
RECEIVED FOR RECORD

'95 DEC 18 PM 2 28

*James D. Young*  
CLERK-REGISTER

LIBER

1 1416

Register of Deeds Stamp & File Number

For corners in

	Kalamazoo (County)	Located In:	Corner Code #
1. Public Land Survey		T 4 S. R 12 W.	B3
		T R	
		T R	
		T R	
2. Property Controlling in Section	S T R		
	S T R		
3. Miscellaneous Property in Sec.	S T R		
	S T R		
4. Lot No. N/A, Recorded Plat N/A			
5. Private Claims			

I, GREGORY N. JENSEN, in a field survey on 07/17, 19 93,  
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned  
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the  
current manual of survey instructions of the United States Department of the Interior, Bureau of Land  
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5  
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a  
Court of Law; established, re-established, monumented, re-monumented, recovered, found as  
expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

B3 NORTH 1/4 POST SEC. 7, T.4 S., R.12 W.

- HODGEMAN FOUND STAKE HOLE AND SET LARGE FLAT STONE WITH DRILL HOLE AND SIDE STONES NORTH AND SOUTH 50 LKS(33') EACH.
- WILKINS AND WEATON PLACED IRON FROM SIDE STONES IN DECEMBER 12, 1939.  
14" HICKORY, N. 63.85'  
SOUTHEAST COR. BARN NW. 104.09'  
IN NORTH AND SOUTH FENCE LINE, SIDE STONES NORTH AND SOUTH 33'
- JOHN KESTER FOUND IRON  
14" HICKORY NORTH 63.85'  
SOUTHEAST COR. BARN NW. 104.09'  
SIDE STONES NORTH AND SOUTH 33'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

B3 NORTH 1/4 POST SEC. 7, T.4 S., R.12 W.

FOUND IRON OVER "T" IRON OVER 3/4" PIPE. KESTER 1972 LCRC L1, P205.

**RATIFIED  
BY KALAMAZOO COUNTY  
REMONUMENTATION  
PEER GROUP**  
11-16-95  
*R. E. G.*

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B3 NORTH 1/4 POST SEC. 7, T.4 S., R.12 W. RATIFIED BY KALAMAZOO COUNTY REMONUMENTATION PROGRAM PEER GROUP ON NOVEMBER 16  
1995. PLACED HARRISON IN MONUMENT BOX OVER 3/4" PIPE AND IS ACCEPTED AS A CAREFUL AND FAITHFUL PERPETUATION OF THE  
POSITION OF THE ORIGINAL CORNER.

SE. COR. BARN NW. - 104.09'  
FACE FENCE POST NORTH - 30.35'  
10" OAK, N 45° E - 35.50'  
NW. COR. OF E. GATE POST S 70° W - 82.9'

Signed by

Surveyor's Michigan License No.

Date