

FEB 26 1998

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

LIBER

2 PAGE 264

CLERK - REGISTER

STATE OF MICHIGAN
COUNTY OF KALAMAZOO
RECEIVED FOR RECORD
97 DEC 23 PM 12 56

Kalamazoo

Located in:

Corner Code#

(County)

Prairie Ronde Township

1. Public Land Survey

T 4S R 12W

G-3

T R

T R

T R

T R

2. Property Controlling
in Section

S

T R

S

T R

3. Miscellaneous

S

T R

Property in Sec.

S

T R

4. Lot No. , Recorded Plat

5. Private Claims

I, Gary D. Hahn, in a field survey on June 28, 1997
do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points
mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required
in the current manual of survey instructions of the United States Department of the Interior, Bureau of
Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3,
4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a
Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed
below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Northeast corner established by U.S. Deputy Surveyor E. H. Lytle.

Witness Ties: Bl. Oak 10 N 54 deg. E 13 L

W. Oak 24 S 84 1/4 deg. W 52 L

1870 - F. Hodgman "Found stone with X planted 25 years ago for corner. Put brick
around."

Date ? - KCRC witness tie notes:

(W) FD. 1.0' below 12-8-39

R.R. iron fence post S 30.32 feet

(W) R.R. iron fence post NW 42.0 feet

(W) 24" Maple N 50 deg. E 51.9 feet

(W) SW corner house NW 103.75 feet

(W) fence to south is east 0.5 feet

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Original monument and accessories not recovered. Found 1/2 inch diameter rebar bent, excavated to find a 5" x 7" flat stone 21"
below road surface and surrounded by bricks. The position of the base of the 1/2 inch bent rebar is over the flat stone and is at the
intersection of the KCRC witness ties to the SW house corner and the RR fence post to the South.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-3, Northeast Corner Section 9, Town 4 South, Range 12 West, ratified by Kalamazoo County Remonumentation Peer Group on
November 20, 1997. Position of base of 1/2 inch iron and intersection of witness ties is accepted as the best available evidence of
the position of the original corner. Set a 20" Harrison Monument in a monument box over the flat stone and in place of bent 1/2
inch rebar.

Witness Ties: RR fence post N 36 deg. W 42.27 feet.

SW corner house N 44 deg. W 103.75 feet.

RR fence post S 33.32 feet

Set PK nail in 8" Twin Maple N 42 deg. E 58.75 feet.

RR spike in power pole S 53 deg. W 50.83 feet.

RATIFIED
BY KALAMAZOO COUNTY
REMONUMENTATION
PEER GROUP
11/20/97 R. Hahn



Signed by

Date

12/19/97

Surveyor's Michigan License No.

38116