

LAND CORNER RECORDATION CERTIFICATE
FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN -:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY.	T. 18 N. R. 13 W.	I-6; I-7; J-7
2. PROPERTY CONTROLLING IN SECTION	14 T. 18 N. R. 13 W.	3; 4
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S. R. E. W.	
4. LOT NO., RECORDED PLAT		
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on June 14, 1978, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on , 19 , found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

XX

C. continued	3	4
Set 5/8"X40" re-rod w/RLS Cap.	Set 5/8"X40" re-rod w/RLS Cap	
15" W.Oak N70°W 36.70'	& Ced.Post w/Loc. Tag.	
7" B.Oak N55°E 31.18'	7" B.Oak Due N 36.3'	
Set Ced.Post w/Loc. Tag	8" B.Oak S05°E 7.2'	
Due W 33'	3" J.Pine Due W 6.4'	
	Old N-S fn. Due W 35'	

- B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:
- I-6 Fd. U.S.F.S. Conc. Mon. that fits equidistant & on line between Sec. Corners to N&S.
 - I-7 Fd. and accepted 3/8" Cabin Spk. in approx. ctr. of E-W Bit. surfaced road & approx. ctr. of N-S gravel roads. Fd. one Geo.H. Johnson Wit.(1928), J.Pine Stump, N66°E, 80.1'.
 - J-7 Fd. & accepted 3/8" Ir. rod in E-W Bit. surfaced road; fits stump remains of two Geo. H. Johnson Wits. (May 1928).
 - 3 Established 1/8 Cor. mid-way and on line between Sec. Cor. to N. & 1/4 Cor. to So. Note: fd. 1/2" re-rod 0.97'-N after setting 5/8" re-rod for 1/8 Cor. (left 1/2" rod in place).
 - 4 Established Ctr. of NW 1/4 of Sec. 14 per Std. B.L.M. instructions.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:		
I-6	I-7	J-7
Fd. U.S.F.S. Conc. Mon. w/brass disk.	Fd. 3/8" Cabin Spk.	Fd. 3/8" iron rod.
7" W.Oak N50°W 81.22	6" B.Oak N40°W 103.76'	10" B.Oak N15°W 39.1
7" B.Oak S80°W 52.35	11" B.Oak S70°W 98.53'	18" B.Oak N60°E 78.7
4"X4" Sq.Post Due W 33'	Set Ced.Post w/Loc. Tag N45°E 70'	Set Ced.Post w/Loc. Tag Due N 33'
Ctr.N-S dirt rd. Due W 4'+	Ctr.E-W Bit.Rd. Due N. 1'+	Ctr. E-W B.Top Rd. Due N. 4.5'+
	Ctr. gravel rds. to N&S Due E. 1'±	Ctr. gravel Rd. Southerly Due E 12'+
		Fn.Cor. (Fn's E&S); 31'-E & 29'-S

SIGNED BY Carl F. Roser 3-27-79 DATE

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES.

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

WEBBER TOWNSHIP
LAKE COUNTY

