

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
LAKE

 (County)

Located In:

Corner Code **##**

- | | | | | | |
|------------------------------------|---|-------------|---|-------------|------------|
| 1. Public Land Survey | T | 18 N | R | 13 W | J-3 |
| | T | | R | | J-4 |
| | T | | R | | |
| | T | | R | | |
| 2. Property Controlling in Section | S | 11 | T | R | 5 |
| | S | | T | R | |
| 3. Miscellaneous Property in Sec. | S | | T | R | |
| | S | | T | R | |

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, **CARL F. ROSER**, in a field survey on **JUNE 11**, 19 **84**, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below.

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

J-3

J-4

5

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

J-3

J-4

5

PREVIOUS DEPT COR OF RECORD;
 CFR 1972. DEPT MON WAS ADDED
 TO RLS, G. BLASS COR OF RECORD
 IN 1972.

MON WAS ADDED TO FD PIPE IN
 1972. THE 2"x 3/4" PIPE WAS A
 COR OF RECORD BY RLS G. BLASS;
 (PREVIOUS DEPT COR OF RECORD -
 CFR 1972).

RECOVERED 1/2" PIPE AS
 ESTABLISHED BY RLS G. BLASS
 (CERT OF SURVEY RECORDED IN
 LIBER 01, PG. 93 & LIBER 105, PG.
 393), FOR THE SW COR N 1/2, NE
 1/4, SEC. 11.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

J-3

J-4

5

D.N.R. MON & CED POST
 * 9" OAK S 75°E 4.6'
 * 8" MAPLE S 30°E 9.6'
 * 11 OAK S 25°W 16.8'
 4 MAPLE N 45°W 20.3'
 CTR WOODS
 TRAIL NW
 & SE DUE N 208'±

D.N.R. MON
 * 36" OAK N 40°E 20.1'
 * 14" OAK S 65°E 74.1'
 * 13" OAK S 45°W 25.0'
 CTR. E-W
 DIRT RD. DUE S 7'±
 SET CED POST DUE N 33'

*EQUALS 1972 D.N.R. MON.

FD 1/2" PIPE, ADDED CED POST
 W/LOC TAG
 15" B. OAK N 25°E 58.3'
 4" W. PINE S 65°E 13.7'
 3" W. PINE S 55°W 14.4'
 CTR. E-W
 DIRT RD. DUE N 15'±
 FD 1/2" PIPE DUE S 33.0'

* EQUALS 1972 D.N.R. MON.

Signed by Carl F. Roser Date 4-12-89

Surveyor's Michigan License No. 12028

