

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. PA 1970

For Corners In: Lake _____ (County)	Located In	Corner Code #
1. Public Land Survey	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S 21 T 19N R 12W	12
	S 21 T 19N R 12W	13
3. Miscellaneous Property in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

4. Lot No: _____ Recorded Plat: _____

5. Private Claims: _____

I, Craig W. McVean, in a field survey on Oct. 15, 2013 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

12 – None.

13 – None.



B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

12 – CS 1/16 Corner Section 21.
Set stamped 2" Aluminum Cap on 5/8" x 34" rebar per
Standard BLM Procedure.

13 – SE 1/16 Corner Section 21.
Set stamped 2" Aluminum Cap on 5/8" x 34" rebar per
Standard BLM Procedure.
East 3.2' to 10' High N-S deer fence

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

12 – Stamped 2" Aluminum Cap on 5/8" x 34" iron rebar
N83°W 44.48' to set N & T in N. side 29" W. Pine
scribed 'XBT'
S13°W 18.04' to set N & T in W. side 16" Red Maple
N77°E 14.48' to set N & T in N. side 12" Red Maple
N18°W 37.48' to set N & T in E. side 9" Red Maple
Set Blue Composite Post with location tag 1' NW

13 – Stamped 2" Aluminum Cap on 5/8" x 34" iron rebar
N30°W 18.19' to set N & T in E. side 22" Red Maple
N55°W 36.05' to set N & T in SW side 5" Red Maple
scribed 'XBT'
S65°W 74.91' to set N & T in N. side 11" Red Maple
scribed 'XBT'
S06°W 62.09' to set N & T in E. side 9" Fir scribed 'XBT'
Set Blue Composite Post with location tag 1' NW

Signed by:

Craig W. McVean

Date:

8/12/2014

Surveyor's Michigan License No.:

39088