

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. PA 1970

For Corners In: Lake (County) Located In Corner Code #
1. Public Land Survey T R
2. Property Controlling in Section S 25 T 19N R 12W 14 SNN1/256
3. Miscellaneous Property in Section S T R
4. Lot No: Recorded Plat:
5. Private Claims:

I, Craig W. McVean, in a field survey on June 12, 2014 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Table with 13 rows and 13 columns (A-M). Contains numbers 1-36 in a grid pattern.

A. Description of original monument and accessories and/or subsequent restoration:

14 - 1991 - LCRC L.3 P.121 - C.F. Roser - fd. 1/2" galv. pipe; SNN1/256 - None
1) 18" B Oak (in clp.) due W 75.4'; 2) 14" B Oak N50°W 67.9';
CTR N-S steel tower elec. transmission line E 43'; CTR N-S trail due W 35'



B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

14 - S1/16 Cor. common to Sec 25, T19N, R12W & Sec 30, T19N, R11W - Fd 1/2" I.D.x18" long iron pipe in CL. of N-S 2-track. SNN1/256 - Cor. Sec. 25 being the NE cor. of the S1/2 of the S1/2 of NE1/4 of the NE1/4 Sec. 25, T19N, R12W - Set 2" alum. cap on 5/8"x34" long rebar per standard BLM procedure. CL of N-S gravel road is 7' E. CL of N-S rebuilt power line is 40' E.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

14 - 1/2" I.D. iron pipe. West 60.00' to set 2" alum. cap on 5/8" x 34" long rebar on Line w/ Blue Composite Post w/ location tag. SNN1/256 - Stamped 2" aluminum cap on 5/8" x 34" long iron rebar. West 33.00' to set 2" alum. cap on 5/8" x 34" rebar on line w/ Blue Composite Post w/ location tag.
N52°W 68.45' to set nail & tag in N side 20" Oak (#2) N15°E 156.41' to 2nd nut & bolt up on W side power pole #3923
N77°W 85.16' to set nail & tag in N side 12" W Pine N87°E 98.11' to set nail & tag in N side 32" W Pine
N10°E 287.17' to 2nd nut & bolt up on W. side power pole #3929 S45°W 79.72' to set nail & tag in SE side 21" W Pine

Signed by: Craig W. McVean
Surveyor's Michigan License No.: 39088

Date: 8/12/2014