

**LAND CORNER RECORDATION CERTIFICATE**  
**Filing Requirement of Act 74, Mich. P.A. 1970**

For corners in  
**LAKE**

(County)

Located In:

Corner Code **##**

1. Public Land Survey	T <u>20N</u> R <u>12W</u>	<u>A-11</u>
	T <u>    </u> R <u>    </u>	<u>B-13</u>
	T <u>    </u> R <u>    </u>	
	T <u>    </u> R <u>    </u>	
2. Property Controlling in Section	S <u>31</u> T <u>    </u> R <u>    </u>	<u>16</u>
	S <u>    </u> T <u>    </u> R <u>    </u>	
3. Miscellaneous Property in Sec.	S <u>    </u> T <u>    </u> R <u>    </u>	
	S <u>    </u> T <u>    </u> R <u>    </u>	

Register of Deeds Stamp & File Number

4. Lot No.         , Recorded Plat           
 5. Private Claims         

I, CARL F. ROSER, in a field survey on 8/15, 19 85, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

A-11

B-13

16

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-11

B-13

16

FD "T" IR FOR NW COR OF SEC 31.

\* = G. BLASS (1948) WITS.

COR FALLS IN CTR OF E-W SAND RD. CTR OF SAND RD N IS 3±W.

FD 1/2" PIPE FOR S 1/4 COR OF SEC 31. FITS THREE 1948 G BLASS WITS. CTR OF SAND RD (IN CURVE) IS 25±N. A STEEL FN POST IR (BURIED 0.8') IS N80°W 12.5'. A 1/2" PIPE (FLUSH-W/ SET CED POST ALONG SIDE) IS N89°50'W, 327.6; ON S LINE S-31. THIS IS SOME KIND OF SEC. SUBN COR(S-31) BY BLASS BET STATE & PVT (NOT SURE OF STATE DESCP, DIDNOT HAVE WITHS)

FD 6 BLASS 1/2"x 18" PIPE FOR SW COR OF SE1/4-SE1/4 OF SEC 31. THE E 1/8 COR ON THE N LINE OF SEC 6(T19N-R12W) IS S89°50' E, 36.70.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-11

B-13

16

FD "T" IR (BURIED 0.4').

FD 1/2" PIPE (BURIED 0.4')

FD 6 BLASS 1/2"x 18" PIPE.

\* 14" W OAK N15°W 29.76  
 \* 14" TWN B OAK S35°E 51.68  
 \* 14" B OAK S20°W 32.24  
 SET CED POST W/LOC TAG SOUTH 33'

\* 10" W OAK N85°E 16.2  
 \* 16" B OAK S25°W 39.8  
 \* 16" B OAK N70°W 28.2  
 \* 11" B OAK N05°W 46.31  
 \* 22" R PINE N20°W 88.76  
 SET CED POST W/LOC TAG N 50'  
 \* = BLASS WITS. N 1/4 COR S-6 (19N-12W) IS S89°50' E, 37.18.

14" OAK N20°W 76.35  
 17" OAK N35°E 78.00  
 SET CED POST W/LOC TAG N 33'  
 COR FALLS IN APPROX CTR OF E-W SAND RD.



Signed by Carl F. Roser 01-28-88 Date         

Surveyor's Michigan License No. 12028