

SECTION

MAR 29 1999

REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Lapeer

(County)

Located In: OREGON TWP.

Corner-Code #

RECEIVED FOR RECORD

99 JAN -6 PM 1:39

Melissa DeVaugh REGISTER OF DEEDS LAPEER COUNTY MICHIGAN

Register of Deeds Stamp & File Number

- 1. Public Land Survey T 8 R 9 K-1
2. Property Controlling in Section S T R
3. Miscellaneous Property in Sec. S T R

- 4. Lot No. Recorded Plat
5. Private Claims

I, MICHAEL G. HAY, in a field survey on MARCH 3 1998, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

Table with 13 rows and 12 columns (A-L) containing numbers 1-36.

A. Description of original monument and accessories and/or subsequent restoration:

1821-JOSEPH WAMPLER D.S. SET POST AT INTERSECTION NB 28 E OF POST W.OAK 24 S45W 23
1864-GILBERT BATES C.S. STAKE-WHITE OAK 24" N50 3/4 E 25'
1972-DWAYNE SCOTT P.S. 12029 L001 P41-42 T-IRON

N65E 55.4' 19" OAK
S60W 32.65' 5" HICKORY
S80W 16.65' USGS MONUMENT 1419 B.M. #38
S30E 78.45' POWER POLE

1974-ROBERT G. KAY P.S. 14096 L003 P.01 T-IRON

N70E 55.4' 18" OAK
S35E 78.45' P. POLE
S60W 32.58' 6" HICKORY

CONTINUED ON BACK

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1998-MICHAEL G. HAY P.S. 41101 FOUND T-IRON AT CENTER LINE CENTER LINE FLINT RIVER ROAD AT NORWAY LAKE ROAD & TREE LINE & OLD FENCE LINE RUNNING WEST, GRAVEL ROADS RUNNING NORTH, SOUTH & EAST. RECOVERED 2 WITNESS CLOSE IN RECORDED MEASURED DISTANCE.

K-1 to J-1 2603.40' (M)
K-1 to K-2 (47.16' [3112.56']) 3110.35' (M) 3110.36' (R-HBE)
K-1 to K-13 2.85' (WEST TO T-IRON)

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-1 SET STANDARD REMONUMENTATION CAP ON SET 1/2" RE-ROD (REPLACED FOUND T-IRON)
N65E 64.37' FOUND P.K. IN SOUTH FACE 18" OAK
S50W 32.49' FOUND NAIL IN BOTTLE CAP NORTH FACE 12" HICKORY
N40W 49.91' SET NAIL NE FACE 8" TWIN MAPLE
S15E 113.40' SET NAIL WEST FACE 22" OAK



Signed by Michael G. Hay Date 12-30-98

Surveyor's Michigan License No. 41101

MAR 29 1999

REVISED MAY 14, 1975
REVISED JAN., 1983
ADAPTED FOR WORD PROCESSING MARCH, 1993

SECTION

1975-ROBERT G. KAY P.S. 14096 L003 P289 T-IRON

N70E 55.40' 18" OAK
S35E 78.45' POWER POLE
S60W 32.58' 6" HICKORY

NOTE: FOUND T-IRON 2.03W & 0.5 NORTH OF WITNESSED NW CORNER

1975-BERNARD HENDERSON P.S. 16043 L2 P133

N70E 55.40' 18" OAK
S35E 78.45' POWER POLE
S60W 32.58' 6" HICKORY

1978-BERNARD HENDERSON P.S. 16043 L4 P708 T-IRON N70E

55.40'
S35E 78.45' POWER POLE
S60W 32.58' 6" HICKORY

*T-IRON 2.00
REMLC 10075
REMYNT 2.00

PEER GROUP
APPROVED AND CORNER

Robert G. Kay
9-17-98