

SURVEY &
REMONUMENTATION

APR 28 1995

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

LAPEER County

Located in:
GOODLAND TOWNSHIP

Corner Code 11

1. Public Land Survey

T 8N R 12E

K11

2. Property Controlling
in Section

S T R

3. Miscellaneous
Property in Sec.

S T R

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

RECEIVED FOR RECORD

95 JAN -3 PM 3:50

LIBER NO. 05 PAGE NO. 205

Melba De Vaughn
REGISTER OF DEEDS
LAPEER COUNTY, MICHIGAN

Register of Deeds Stamp & File Number

I, JAMES T. BAILEY, in a field survey on OCTOBER 13, 19 94, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G.L.O. (1824) L. LYON SET POST 18" BEECH S.19°E. 5 LKS, 10" NUT TREE N.66°W. 26 LKS
SURVEY (1972) KAY P.S. LIBER 001, PAGE 400, NO OBJECT STATED, 3 WITS GIVEN
SURVEY (1973) KAY P.S. LIBER 002, PAGE 474
SURVEY (1985) KAY P.S. UNRECORDED, FD. 1/2" IRON, 3 WITS GIVEN
SURVEY (1993) ELRICH P.S. LIBER 010, PAGE 115, FD. 1/2" IRON, 4 WITS. GIVEN

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1994 JAMES T. BAILEY P.S. FOUND 1/2" ROD 10" BELOW GRADE IN THE INTERSECTION OF NORMAN AND WHEELING ROADS. FOUND 2 WITNESSES SAME AS THE 1985 AND 1993 SURVEYS THAT VERIFY THE LOCATION OF THE 1/2" ROD FOUND.

ACCEPTED 1/2" ROD AS BEST LOCATION OF ORIGINAL POSITION OF THE NORTHEAST CORNER, SECTION 35, T8N-R12E, GOODLAND TOWNSHIP.


APPROVED LAND CORNER
PA 345 OF 1990
LAPEER COUNTY

JAMES T. BAILEY
PROFESSIONAL SURVEYOR
DATE 1-3-95

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-11 SET STANDARD REMONUMENTAION CAP ON FOUND 1/2" ROD.

N.75°W. 111.03 SET NAIL W/ REMON TAG IN SOUTH FACE 34" OAK
N.20°E. 110.91 SET NAIL W/ REMON TAG IN WEST FACE 20" OAK
N.50°E. 53.50 SET NAIL W/ REMON TAG IN SOUTH FACE 38" OAK
S.45°W. 65.40 SET NAIL W/ REMON TAG IN N.W. FACE P.P.
N.75°W. 111.53 FD. 16 "D" NAIL IN SOUTH FACE 34" OAK
N.50°E. 53.22 FD. 16 "D" NAIL W/ BOTTLE CAP IN SOUTH FACE 38" OAK



Signed by James T. Bailey Date DECEMBER 29, 1994
Surveyor's Michigan License No. 33968