

# SURVEY & REMONUMENTATION

FEB 16 1999

## SECTION

Filed under Remonumentation Act 345 of 1990  
**LAND CORNER RECORDATION CERTIFICATE**  
 Filing Requirement of Act 74, Mich. P.A. 1970

LIBER 1 PAGE 299  
 STATE OF MICHIGAN  
 LENAWEE COUNTY  
 FILED

10 DEC 1998 9:47:03 AM

VICTORIA J. DANIELS  
 REGISTER OF DEEDS

For corners in

Lenawee  
 (County)

Located In:

Corner Code #

1. Public Land Survey

T - R -  
 T R  
 T R  
 T R

2. Property Controlling in Section

S 18 & 19 T - 5 - S R - 3 - E

3

3. Miscellaneous Property in Sec

S T R  
 S T R  
 S T R

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

I, Glenn E. Richard, in a field survey on October 21, 1998, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G.L.O. This position not established by original government surveyors  
 The original patent from the U.S. to Montgomery Crofoot was for the Middle Subdivision of the SW 1/4 of Sec 18 and this is the SW corner  
 1882 James Blair set a stake for this corner  
 1064 Walter Frazier surveyed lot in N 1/2 of the Middle Subdivision of the SW 1/4, Sec. 18  
 1970 I set a re-rod for the SW corner of the Middle Subdivision of the SW 1/4 of Sec 18 in line with the center line of Munger Road to the east and a line extended South 33' West of East R.O.W. iron set by Mr. Frazier to the North in 1964  
 1992 I found the re-rod and measured North to the NW cor of the SW corner of the Middle Subdivision of the SW 1/4 of Sec 18. Meas. 2623.28 One of Blairs records shows the distance as 2613.60' and another at 2640'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

September 21, 1998 I found the re-rod and set a monument box  
 October 21, 1998 I replaced the 1/2" re-rod with a 5/8" X 3' re-rod with Lenawee County Remon cap stamped P.S. 13040

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

5/8" X 3' re-rod with Lenawee County Remon cap stamped P.S. 13040 in monument box.  
 This position not established by original government surveyors. This monument is accepted as the best available evidence of the position of the corner.

Dbl. hd. nail & remon tag in 30" Maple N 20°E 89.63  
 Survey mark spike & remon tag in Elec Pole S 60° E 83.29  
 P.K. nail and remon tag in Elec pole S 40° W 37.48  
 Re-rod at road R.O.W. intersection N 35° W 46.54



Ratified by Peer Group in accordance with P.A. 345 Co. Rep. Glenn E. Richard Date 11-3-98

Signed by Glenn E. Richard Date Nov. 10, 1998  
 Glenn E. Richard

Surveyor's Michigan License No. 13040

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971

REVISED MAY 14, 1975

REVISED JAN. 1983

ADAPTED FOR WORD PROCESSING MARCH 1993