

JAN 22 2001

Filed under Remonumentation Act 345 of 1990

SECTION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Lenawee
(County)


Located in:

Corner Code #



LIBER 2

PAGE 27



1. Public Land Survey T-6-S R-3-E L-9
 T R
 T R
 T R
 T R
2. Property Controlling S T R
 in Section S T R
3. Miscellaneous S T R
 Property in Sec S T R

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Glenn E. Richard, in a field survey on November 13, 2000, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

A B C D E F G H I J K L M

1													
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G.L.O. 1824 John M. Mack D.S. Set 1/4 Sec. post B. Ash 15 N 7 W 80 Willow 12 S 59 E 76
 Could not find any information on this corner prior to 1927
 1927 Fred Soll P.S. 1090 surveyed the Girls Training School in Sections 25 and 26 for the State of Michigan. "Accepted and monumented fence corner"
 1929 Walter Frazier began survey at this corner & listed witnesses the same as Fred Soll's survey
 1956 While employed by Walter Frazier I found brass capped monument
 1971 Kenneth Suydam found "State Monument"
 1976 Werner Sommer found brass capped monument and recorded it in Liber 3, Page 480. Nail & disc in 18" Sycamore S 25° E 75.41
 1957 & 1982 MDOT surveys for M-52 "Found State of Michigan Standard Brass Disc" 18" Sycamore S 14° E 75.35
 2000 The Plat of The Woods of West Valley is tied to this corner.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Nov. 13, 2000 Found "State of Michigan" monument in swamp. Top of monument level with the water level.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Brass cap stamped "State of Michigan" monument and is accepted as the best available evidence of the position of the original corner.

dbl hd nail and re-mon tag in 12" Oak S 55° W 68.37
 dbl hd nail and re-mon tag in 10" Ash S 15° W 47.19
 Set dbl hd nail and re-mon tag in 21" Sycamore S 15° E 75.36
 Angle iron post N 0.67
 Carsonite post West 0.54



Ratified by Peer Group in accordance with P.A. 345 Co. Rep. Glenn E. Richard Date November 28, 2000

Signed by Glenn E. Richard Date Nov. 30, 2000
 Glenn E. Richard

Surveyor's Michigan License No. 13040