FEB 23 2001

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970


Luce County Remonumentation Corner

SECTION

For corners in Luce County Located in: Corner Code # T45N R12W A-2` 1. Public Land Survey Same T45N **R13W** Corner Т R Ţ R Т 2. Property Controlling S R COLA in Section S T R Miscellaneous S T R Property in Sec. S R , Recorded Plat 5. Private Claims WMEN

 LUCE COUNTY REGISTER OF DEEDS Recorded page 939 .ber 3 02-12-2001, 09:41:4 in the Kathy S. Wahar, Register REGISTER OF DEEDS

Register of Deeds Stamp & File Number



I, William L. Karr, in a field survey on August 9, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(A-2) 1/4 Corner common to Section 6, Township 45 North, Range 12 West and Section 1, Township 45 North, Range 13 West.

John Burt set post for corner. <u> 1841</u>

Sugar 17

S76E

N39W 36

Beech 5 1986 G. Wiggins, P.S. 23251 set DNR monument for corner by single proportionate measurement and recorded in Liber 2 Page 34 of the Schoolcraft County Corner records. Witnesses:

8" H. Maple S67°W 13.2 feet 10" H. Maple N31°E 18.5 feet

8" H. Maple N03°W 15.5 feet 12" H. Maple S84°E 22.8 feet

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: (A-2) 1/4 Corner common to Section 6, Township 45 North, Range 12 West and Section 1, Township 45 North, Range

This corner is being re-established as part of the Luce County Remonumentation Program.

The 1986 DNR resurvey of the range line inadvertently used a witness pipe at Section Corner 18, 19, 24 and 13 to prorate against. This caused five corners re-established in that survey to be South and East of their true prorated position.

Found a 1 1/2" pipe with 4" aluminum Michigan Department of Natural Resources cap 4.57 feet South and 3.65 feet East of prorated position. Contacted MDNR and reset Michigan Department of Natural Resources monument by single proportionate measurement using section corner 18, 19, 24 and 13, 2 1/2 miles to the South and the Township corner 1/2 mile to the North. Distance South is 13,233.40 feet (GLO - 13,200 feet). Distance North is 2585.14 feet (GLO - 2578.62 feet).

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: (A-2) 1/4 Corner common to Section 6, Township 45 North, Range 12 West and Section 1, Township 45 North, Range 13 West.

Corner is a 1 1/2" pipe 4" aluminum Michigan Department of Natural Resources cap, driven over a 1/2" x 48" re-rod.

Witnesses:

Sugar Maple 12"	N05°E	11.31 feet	(Previous)
Sugar Maple 13"	N49°E	17.87 feet	(Previous)
Sugar Maple 16"	S79°E	27.64 feet	(Previous)
Sugar Maple 12"	S33°W	13.62 feet	(Previous)

Bearings are compass bearings, corrected for declination (6° W),

all distances are to a nall and tag in the side of the witness object unless otherwise noted.

Signed by William L. Karr, P.S.

12/01/ Date



Surveyor's Michigan License No. 27450