

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Form with fields for Luce (County), Located In, Corner Code #, and sections 1-5: Public Land Survey, Property Controlling in Section, Miscellaneous Property in Sec., Lot No., Recorded Plat, Private Claims.

Register of Deeds Stamp & File Number

Table with 13 rows and 13 columns (A-M) for recording deed stamps and file numbers.

I, Stephan J. Szyszkoski, in a field survey on 06/29/2010 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(16-Sec. 6) East 1/16 corner between Sections 6 and 7. Not established in the original survey.

(1-Sec. 7) West 1/16 corner between Sections 6 and 7. Not established in the original survey.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(16-Sec. 6) Established the corner midway and on the Section line between Section corner 1321.79' east and Quarter corner 1321.79' west.

(1-Sec. 7) Established the corner on the Section line between Sections 6 and 7 1246.86' east of Section corner A3 and 1324.33' west of Quarter corner B3, being proportionate to the dimensions shown on the original plat.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(16) Set 1"IDx36" I.pipe with 4" alum. MDNR cap. Set measuring nail with MDNR tag in the side of: 5" Tamarack S55W 26.9' mrkd "E1/16 BT" 5" W.Pine N01E 25.2' do 7" Tamarack N24E 22.45' do 6" B.Spruce S39E 12.55' do Bearings are magnetic.

(1) Set 1"IDx36" I.pipe with 4" alum. MDNR cap. Set measuring nail with MDNR tag in the side of: 10" Cedar S01E 6.25' mrkd "W1/16 BT" 8" Cedar S59W 14.5' do 13" Cedar N29E 7.6' do 8" Cedar N85E 11.3' do Bearings are magnetic.

Signed by [Signature] Surveyor's Michigan License No. 33986

Date 10/26/2010

For the Michigan Department of Natural Resources and Environment, Forest Management Division

