

MAR 17 2000

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

FILED

For corners in

SECTION

For corners in

LIVINGSTON

(County)

Located In:

Corner Code #

1. Public Land Survey

T I N R 3 E

G-10

2. Property Controlling in Section

§
§

T	R
T	R

3. Miscellaneous

S

T R

Property in Sec.

§

T R

4. Lot No. _____, Recorded Plat _____

5. Private Claims

I, DARRILL D. HUGHES, in a field survey on NOVEMBER 3, 1999 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO: 1825 Sylvester Sibley, Deputy Surveyor
BLACK OAK 15" N73E 48 LINKS
BLACK OAK 16" S50W 42 LINKS

* ADDITIONAL HISTORICAL INFORMATION ON BACK OF SHEET

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 1/2" IRON ROD 6' SOUTH OF SOUTH EDGE E/W ASPHALT PAVEMENT
0.4' BELOW GRAVEL GRADE. OCCUPATION NORTH AND SOUTH.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-10, T1N, R3E, UNADILLA, set corner with 3/4" x 36" iron pipe, affixed with 2" dia. Brass disk. Disk stamped "Livingston Co. Monumentation Corner, 19834" and is accepted as a careful and faithful reestablishment of the position of the original corner.

177 DEGREES 33.35' SET NAIL/TAG E/S UTILITY POLE.
321 DEGREES 69.48' SET NAIL/TAG E/S 30" POPLAR.
021 DEGREES 52.08' SET NAIL/TAG W/S 8" PINE.
115 DEGREES 84.92' SET NAIL/TAG SW/S 6" TWIN APPLE.

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY
PEER GROUP ON 9-15-99, CO. REP JED

Signed by

Date NOVEMBER 3, 1999

Surveyor's Michigan License No. 19834