

## FEB 26 2001

FILED

For comers in

## SECTION

LIVINGSTON

(County)

**Located In:**

Corner Code #

## 1. Public Land Survey

T 1N R 3E

**I-07**

T	R
---	---

T R

T R

T R

## 2. Property Controlling in Section

S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

### 3. Miscellaneous Property in Sec

S I R

S T R

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

## 5. Private Claims

I, DARRELL D. HUGHES, in a field survey on October 17, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE:** Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

**GLO:** 1825, Sylvester Sibley, Deputy Surveyor

White Oak 17 inch diameter, bears North 86 degrees West, 50 links

Black Oak 22 inch diameter, bears North 46 degrees East, 48 links

\* ADDITIONAL HISTORICAL INFORMATION ON BACK OF SHEET

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1/2 inch iron rod inside 1 inch iron pipe

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

**I-07, T1N, R3E, UNADILLA,** replaced existing corner with 1-1/4" x 36" iron pipe, affixed with 2" diameter brass cap, stamped "Livingston Co. Monumentation Corner, P.S. 19834," and is accepted as a careful and faithful reestablishment of the position of the original corner.

083 DEG. 35.32' SET NAIL/TAG N/S 24" MAPLE

356 DEG. 52.17' SET NAIL/TAG E/S 42" OAK

200 DEG. 51.30' SET NAIL/TAG E/S 15" CHERRY

247 DEG. 51.32' SET NAIL/TAG N/S 20" OAK

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY

PEER GROUP ON 9-6-00 CO. REP. JED

**Signed by**

Surveyor's Michigan License No. 19834

Date \_\_\_\_\_

October 17, 2000