

SURVEY & REMONUMENTATION

FEB 26 2001

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

SECTION

LIVINGSTON

(County)

Located In:

Corner Code #

1. Public Land Survey

T 1N R 3E

I-08

T R

T R

T R

2. Property Controlling in Section

S T R

T R

3. Miscellaneous Property in Sec.

S T R

T R

S T R

T R

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

FILED

2000 NOV 15 A 9:30

NANCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI.
48843

LSC #1380m

Register of Deeds Stamp & File Number

I, DARRELL D. HUGHES, in a field survey on October 18, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO: 1825, Sylvester Sibley, Deputy Surveyor
White Oak 18 inch diameter, bears North 70 degrees, 268 links

A	B	C	D	E	F	G	H	I	J	K	L
1											
2	6		5		4		3		2		1
3											
4	7		8		9		10		11		12
5											
6	18		17		16		15		14		13
7											
8	19		20		21		22		23		24
9											
10	30		29		28		27		26		25
11											
12	31		32		33		34		35		36
13											

UNADILLA TWP.

* ADDITIONAL HISTORICAL INFORMATION ON BACK OF SHEET

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
Found 1/2 inch iron rod

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY
PEER GROUP ON 9-6-00 CO. REP JED

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-08, T1N, R3E, UNADILLA, replaced existing corner with 1-1/4" x 36" iron pipe, affixed with 2" diameter brass cap, stamped "Livingston Co. Monumentation Corner, P.S. 19834," in road box and is accepted as a careful and faithful reestablishment of the position of the original corner.
087 DEG. 128.75' SET NAIL/TAG S/S 6" ROUND WOOD POST
319 DEG. 119.61' SET NAIL/TAG SW/S UTILITY POLE
114 DEG. 176.34' SET NAIL/TAG N/S 8" OAK
014 DEG. 28.35' SET PK NAIL/TAG TOP OF NORTH END 15" CMP CULVERT

Signed by

Surveyor's Michigan License No. _____

19834

Date October 18, 2000