

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Livingston  
(County)

Located In:

Corner Code #

1. Public Land Survey

T 1N R 4E

K-12

T \_\_\_\_\_ R \_\_\_\_\_

T \_\_\_\_\_ R \_\_\_\_\_

T \_\_\_\_\_ R \_\_\_\_\_

2. Property Controlling  
in Section

S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

3. Miscellaneous  
Property in Sec.

S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

Dec 27 12 22 PM '93  
NANCY HAYLAND  
REGISTER OF DEEDS  
LIVINGSTON COUNTY, MI  
48843

FILED

L.S.C. #112m

Register of Deeds Stamp & File Number

I, Darrell D. Hughes, in a field survey on December 16, 19 93,  
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned  
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the  
current manual of survey instructions of the United States Department of the Interior, Bureau of Land  
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5  
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a  
Court of Law; established, re-established, monumented, re-monumented, recovered, found as  
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO: 1823

White Oak 12" N53E 80 lks.

White Oak 12" N75W 92 lks.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	16		17		18		19		20		21		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

\* Additional historical information on back of sheet:

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Fd. 4" diameter concrete monument and 1/2" iron rod.

SURVEY &  
REMONUMENTATION

1993

COMMISSION

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-12, T1N, R4E, PUTNAM, replaced existing concrete monument and 1/2" iron  
rod with 1-1/4" X 36" iron pipe, affixed with 2" dia. brass cap, stamped  
"Livingston Co. Monumentation Corner, P.S. 19834, and is accepted as a  
careful and faithful reestablishment of the position of the original  
corner.

060 DEG. 14.89' SET NAIL/TAG NW/S 24" OAK.

137 DEG. 50.05' SET NAIL/TAG NE/S 18" OAK.


180 DEG. 29.82' SET NAIL/TAG E/S 30" OAK.

230 DEG. 38.48' SET NAIL/TAG NW/S 14" OAK.

Signed by Darrell D. Hughes  
Surveyor's Michigan License No. 19834

Approved by Liv. Co. Peer Group: Nov. 20, 1993  
Date December 27, 1993

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971



PUTNAM TOWNSHIP, T1N, R4E

K-12, West 1/4 corner Section 36

Field 10-26-93, 11-16-93 D.D. HUGHES AND ASSOCIATES

Found 4" diameter concrete monument with 1/2" iron rod. Monument leans to Northwest. Found 1/2" iron (also hit) 0.80' Southeast from leaning Monument. Witness' as shown fall between Monument and 1/2" rod. If monument straight, would match 1975 Benton ties.

Joseph Wampler first set corner in 1823.

1969, Garlock shows corner as fence post.

1974, Oscar Boss set 1/2" iron at fence corner.

1975, Pat Benton found Boss iron and witnessed

1976, Boss filed Act 74 showing 1974 ties.

1990, Corner shown as corner of "PORTAGE BAY HIGHLANDS NO.3", subdivision. Boss.

A traverse was run to monumentation in "Portage Bay Highlands No. 3" to verify location of corner. The leaning 4" diameter concrete monument and iron rod will be removed and replaced with standard Livingston County Remonumentation monument at plat distances. This corner will match 1975 Benton witness'.