

SURVEY & REMONUMENTATION

FEB 26 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

FILED

For corners in

<u>LIVINGSTON</u> (County)	Located In:	Corner Code #
1. Public Land Survey	T 1 N R 4 E	E-08
	T R	
	T R	
	T R	
2. Property Controlling in Section	S T R	
	S T R	
3. Miscellaneous	S T R	
Property in Sec.	S T R	

2000 SEP 28 A 9:17

NANCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI.
48843

LSC#1273m

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, JACK K. SMITH, in a field survey on AUGUST 25, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A	B	C	D	E	F	G	H	I	J	K	L	M
1												
2	6		5		4		3		2		1	
3												
4	7		8		9		10		11		12	
5												
6	18		17		16		15		14		13	
7												
8	19		20		21		22		23		24	
9												
10	30		29		28		27		26		25	
11												
12	31		32		33		34		35		36	
13												

A. Description of original monument and accessories and/or subsequent restoration:

GLO 1825 JOSEPH WAMPLER SET POST
BLACK OAK 10" N39°W 34.98'
WHITE OAK 20" S80°E 47.52'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

THE EXISTING CORNER IS A 1/2" REROD SET AT 1/2 THE DISTANCE ON LINE BETWEEN CORNERS E-07 AND E-09.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-08 WEST 1/4 CORNER SECTION 21, T1N, R4E, PUTNAM TOWNSHIP, LIVINGSTON COUNTY, MICHIGAN:
SET 1 1/4" x 36" STEEL PIPE WITH LIVINGSTON COUNTY REMONUMENTATION BRASS CAP STAMPED SURVEYOR #35999 IN PLACE OF 1/2" REROD.

N80°W	SPIKE AND REMON TAG ON SOUTH SIDE OF 12" OAK	9.12'
N20°E	SPIKE AND REMON TAG ON WEST SIDE OF 12" OAK	54.42'
N80°E	SPIKE AND REMON TAG ON SOUTH SIDE OF 14" OAK	71.09'
S40°E	SPIKE AND REMON TAG ON WEST SIDE OF 10" OAK	30.12'
S20°W	SPIKE AND REMON TAG ON WEST SIDE OF 10" CEDAR	7.81'



Signed by

Jack K. Smith

Date

9-15-2000

PA. 345 1990, APPROVED BY LIVINGSTON COUNTY

Surveyor's Michigan License No. 35999

PEER GROUP ON 2-2-2000 CO. REP. LED