SURVEY & REMONUMENTATION

FEB 2 6 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE

FILED

		Filing	Kequireme	nt of Act 14,	WICH. F.A.	1370					
For corners in LIVINGSTON		Located in:	HAMBLIBG	Corner Code	#	2000 OCT 19 A 10: 32					
(Count	y)	. Located in:	MARIDONG	00.110. 0000	"						
1. Public Lan	d Curvey	т 1N	. R 5E	F-7			NA REC	NCY HA	VILANI	0	
1. Public Lan	u Survey		R		1		LIVINO	išton č	DUNTY	, ML	
			_ R					4884	3	,,	
			. R								
2. Property C	ontrolling S	3 T				/					
in Section		5TT						1316M			
3. Miscellane		STT			j	Register o	f Deeds	s Stamp	and Fil	e Numl	bei
Property in	Sec. S	S T	_ R		L						
4 Let No	Rec	orded Plat									
							A B	CDE	F G	н	+
5. Private Cit	auris						. <u> </u>		_	- 1	1-2-
				•		. 3	lí	 	1	1-1-	1
Bryan L. Boss		a field survey on	N	MARCH 15, 2000			l I		_		 13
do hereby certify	, that under requir	a field survey on rements of P.A. 74	. Michigan P.A	A. of 1970, the co	orner points me		1 4	<u> </u>	<u> </u>	11	+
in lines 1 and 2	above were in	conformance with	n regulations	and rules therei	for as required	in the	1 1	<u> </u>	- 16	- 15	ا 14'
current manual	of survey instruc	ctions of the Unit	ted States Dep	partment of the in	nterior, Bureau (of Land 4 and 5	,		-	4-1-	+
Management or	by a decree of a	Court of Law and/ the rules of the	or that the co Michigan Boar	rner points menti d of Land Survev	ors or by a Dec	ree of a	1 1	1 20 -1	-21	-22	1 123
Court of Law;	established, re-	established, mon	umented, re-	monumented, re	ecovered, four	nd as	, 🗐	1 1 1	4		+
expressed below	<i>i</i> .					11	-30-		-23-	-27 -	- 26 - 26
NOTE: Not m	ore than 4 corn	ers, all in the sar	ne town and	range, may be	recorded	1	1 1	╁┼┼┼		- -	╁
on un	is certificate.					1.	2 - 31 -		-33	-34-	-35
A Department	n of original mo	nument and acce	ecories and/	or subsequent i	restoration:	1	3				ㅗ
	. SIBLEY, DEPUT		,5301103 01107	or adbacquorite							
SET POST		1 SURVETUR									
B. OAK 12	" N 46° E 1.16 CH										
B. OAK 5"	S 70° E 1.14 CHA	INS	·								
B. Descriptio	n of corner evid	lence found and/	or method ar	plied in restoria	ng or reestabl	ishing co	rner:				
		FENCE LINE +/- 60									
GROUND											
				•							
			٠.	•							
		•									
			•								
					•						
	•			م من المصادا المساد	emetusta laar	sting the	naeitian	of the c	orner:		
		t for corner and a		stablished to p	erpetuate loca	ating the	positioi	101 1110 1	,0,1,101.		
		BRASS CAP STAN MONUMENTATION									
CORNER	WITH CARSON	TE MARKER			•						
	2.10' SET REMON	I NAIL/TAG S/SIDE	20"	•							
OAK EAST 66.	98' SET REMON N	NAIL/TAG N/SIDE 2	0" OAK	i i				:			
. S 45° E 7		I NAIL/TAG W/SIDE			٠,						
STUMP S 30° E 6	0 57' SET REMON	I NAIL/TAG SW/SID	E 22"				الاست	000mm.			
TAMARA						-	e OF	MICHIG	L .		
	•					- A	***************************************	70	. T.		
						1×1	BRY	AN L.	7.1		
				•		# ::/	BC	88	14	į	
						1		Utveyor]*		
PΔ	345 1990. APPI	ROVED BY LIVING	STON COUN	TY		12		D. 238	/_}	•	
		-1-2000 co.				181	_		0		
ecch	THE TOP ON	,	1161 			3	ED EAN	EURY	*		
						7	4	10	•		

Date

29238

Surveyor's Michigan License No.