

# LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

| FOR CORNERS OF--                                                             | LOCATED IN-- | CORNER CODE NUMBER |
|------------------------------------------------------------------------------|--------------|--------------------|
| 1. PUBLIC LAND SURVEY <u>11</u> T. <u>1</u> N. S., R. <u>6</u> E. W.         |              | K-3, K-4           |
| 2. PROPERTY CONTROLLING IN SECTION _____, T. _____, N. S., R. _____, E. W.   |              |                    |
| 3. MISCELLANEOUS PROPERTY IN SECTION _____, T. _____, N. S., R. _____, E. W. |              |                    |
| 4. LOT NO. _____, RECORDED PLAT _____                                        |              |                    |
| 5. PRIVATE CLAIMS _____                                                      |              |                    |

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Donald L. Bissell, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on July, 1979, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_, 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

K-3 Found brick nail as called for in notes received from Washtenaw Engineering. K-4 Found 3/4" iron pipe with plastic cap.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-3 Set 3/4" pipe with plastic cap. N 26° E 125.45' Face of 10" steel post N 74° E 34.34' P.P. Spike and Tag N 13° E 189.35' Face of 10" steel post [ Kensington Road K-4 3/4" pipe with plastic cap. N 56° W 49.33' Tele. pole Spike & Tag N 77° E 14.73' 10" B. Cherry Spike & Tag S 62° E 14.87' 3" B. Cherry Spike & Tag

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_ (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

APPROVED AND SIGNED BY Donald L. Bissell DATE 12-19-79  
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. 18655

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971  
REVISED MAY 14, 1973