

File Livingston Co. 1106

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN-:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY <u>5</u> T. <u>1</u> N. <u>2</u> , R. <u>6</u> E. <u>3</u>		<u>D-3, E-3</u>
2. PROPERTY CONTROLLING IN SECTION _____, T. _____, N. _____, S. _____, R. _____, E. _____, W. _____		
3. MISCELLANEOUS PROPERTY IN SECTION _____, T. _____, N. _____, S. _____, R. _____, E. _____, W. _____		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Dwayne Scott, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on August, 1975, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on August, 1975, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

D-3 Recovered 1/4" Iron Pipe	E-3 Recovered 3/4" Iron Pipe
M.D.S.H. Witnesses	M.D.S.H. Witnesses
N. 39°W. 19" Oak 64.00'	S. 82°E. 22" Oak 38.22'
N. 57°W. 28" Elm 97.90'	N. 55°E. 4" Oak 22.73'
West FePost 62.25'	N. 08°W. 20" Oak 29.15'
East FePost 87.45'	N. 32°W. 25" Oak 27.45'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-3 1/4" Iron Pipe with Plastic Cap #12029	E-3 3/4" Iron Pipe with Plastic Cap #12029
S. 45°W. 91.22' Tele. Pole	S. 04°W. 37.57' 14" B. Oak
West 62.28' Fe.Post	S. 80°E. 38.10' 32" B. Oak
East 27.0' Center line Pavement	N. 05°E. 9.20' 12" B. Cherry
South 32.0' Center line Maltby Road	N. 72°W. 34.10' 20" B. Oak
S. 55°E. 62.60' U.S. Bench Mark (4FWK)	

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Dwayne Scott CHIEF OF SURVEY PARTY DATE Dec 1976
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. 12029