

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Livingston  
(County)

Located In:

Corner Code #

1. Public Land Survey

T R

T R

T R

T R

2. Property Controlling  
in Section

S 36 T 1N R 6E

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

L-11-2

L.S.C. #162m  
Register of Deeds Stamp & File Number

Dec 29 8 09 AM '93  
NANCY HAYLAND  
REGISTER OF DEEDS  
LIVINGSTON COUNTY, MI  
48843

FILED

4. Lot No. , Recorded Plat

5. Private Claims

I, H. Lawrence O'Donnell survey on December 28, 1993,  
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned  
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the  
current manual of survey instructions of the United States Department of the Interior, Bureau of Land  
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5  
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a  
Court of Law; established, re-established, monumented, re-monumented, recovered, found as  
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO Survey November 1815 by Joseph Wampler  
Set qr. post in marsh  
No bearing trees

(Additional historical data on back of sheet)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Corner now falls in Nichwagh Lake, position re-established  
using surveys of record (see back of sheet) at 2685.12 feet  
East of NW corner Section 36.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 1½" X 36" Iron Pipe with brass cap on East side of  
Nichwagh Lake 902.46' West of NE Cor. Section 36, T1N,  
R6E, 4 feet North of North edge of Nine Mile Road

4" Oak N10°W 22.18' to nail w/flasher  
4" Oak N70°E 44.26' to nail w/flasher  
4" Oak N45°W 50.67' to nail w/flasher  
20" Box- South 44.91' to nail w/flasher  
elder



Signed by H. Lawrence O'Donnell Date December 28, 1993

Surveyor's Michigan License No. 28419

Approved by Livingston County Monumentation Peer Group November 17, 1993

Civil Engineering • Surveying  
Planning • Environmental Services

# A T W E L L - H I C K S, I N C.

540 Avis Drive  
P.O. Box 2981  
Ann Arbor, Michigan 48106  
313 994 4000 • FAX: 313 994 1599

## RESEARCH SUMMARY

L-11, 1/4 Corner Section's 25, T1N, R6E  
36

The location for this corner now falls in Nichwagh Lake. Original GLO notes called for 1/4 post set at 40.15 in marsh and no bearing trees.

In 1957, Atwell-Hicks, Inc. set a point for the 1/4 corner 2682.80 feet East of the NW Corner Section 36, in drained lake bottom.

A 1969 survey by Washtenaw Engineering shows the corner falling in the lake as do all subsequent surveys.

A 1973 survey by Washtenaw Engineering computed the point to fall 2685.12 feet East of the of the NW corner. Other surveys using the same 2685.12 measurement are Boss Engineering plats of Eagle Cove and Eagle Cove No. 2; Atwell-Hicks, Inc. plats of Nichwagh Lake Estates and Nichwagh Lake Estates No. 2; a 1992 survey by Atwell-Hicks, Inc. and a 1993 survey by Boss Engineering.

Accessory corners will be st on each side of Nichwagh Lake on the North line.

I recommend maintaining the location of the corner at the 2685.12 feet east of the NW corner.



Mary A. Borkowski, RLA • William C. Henderson • Robert J. Jagow Jr., PE, PS • Robert G. Macomber, PE, PS  
John L. Snyder, PE, PS • Allen R. Suggitt, PE • Richard G. Timmons, PE, PS