

SURVEY & REMONUMENTATION

FEB 26 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

FILED

2000 NOV 15 A 9:29

NANCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI.
48843

LSC #1371m

Register of Deeds Stamp & File Number

LIVINGSTON Located In: Corner Code #
(County)

1. Public Land Survey T 2 N R 3 E F-09
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, DARRELL D. HUGHES, in a field survey on October 30, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L
1												
2		6		5		4		3		2		1
3												
4		7		8		9		10		11		12
5												
6		18		17		16		15		14		13
7												
8		19		20		21		22		23		24
9												
10		30		29		28		27		26		25
11												
12		31		32		33		34		35		36
13												

IOSCO TWP.

A. Description of original monument and accessories and/or subsequent restoration:

GLO: 1825, Sylvester Sibley, Deputy Surveyor
White Oak 20 inch diameter, bears North 11-1/2 degrees East, 47 links
Aspen 9 inch diameter, bears South 4-1/2 degrees East, 19 links

* ADDITIONAL HISTORICAL INFORMATION ON BACK OF SHEET

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1/2 inch iron rod

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

F-09, T2N, R3E, IOSCO, replaced existing corner with 1-1/4" x 36" iron pipe, affixed with 2" diameter brass cap, stamped "Livingston Co. Monumentation Corner, P.S. 19834," and is accepted as a careful and faithful reestablishment of the position of the original corner.

032 DEG. 8.89' SET NAIL/TAG SE/S 20" TWIN HICKORY

313 DEG. 35.69' SET NAIL/TAG S/S 32" OAK

192 DEG. 10.34' SET NAIL/TAG E/S 4" ASH

138 DEG. 41.87' SET NAIL/TAG NE/S 10" HICKORY

PA. 345 1990, APPROVED BY LIVINGSTON COUNTY
PEER GROUP ON 9-20-00 CO. REP JED

Signed by Darrell Hughes
Surveyor's Michigan License No. 19834

Date October 30, 2000