

SURVEY &
REMONUMENTATION

FEB 26 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

FILED

For corners in

LIVINGSTON

(County)

Located In:

Corner Code #

1. Public Land Survey

T 2 N R 3 E

G-07

T R

T R

T R

2. Property Controlling
in Section

S

T R

S

T R

3. Miscellaneous
Property in Sec.

S

T R

S

T R

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

2000 NOV 15 A 9:30

NANCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI.
48843

LSC #1372m

Register of Deeds Stamp & File Number

I, DARRELL D. HUGHES, in a field survey on October 31, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO: 1825, Sylvester Sibley, Deputy Surveyor

White Oak 11 inch diameter, bears North 82-1/2 degrees West, 526 links

White Oak 14 inch diameter, bears South 01 degrees East, 836 links

IOSCO TWP.

* ADDITIONAL HISTORICAL INFORMATION ON BACK OF SHEET

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1/2 inch rod

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-07, T2N, R3E, IOSCO, replaced existing corner with 1-1/4" x 36" iron pipe, affixed with 2" diameter brass cap, stamped "Livingston Co. Monumentation Corner, P.S. 19834," and is accepted as a careful and faithful reestablishment of the position of the original corner.

043 DEG. 70.37' SET NAIL/TAG SE/S 6" ASH

132 DEG. 60.27' SET NAIL/TAG SW/S 18" ASH

247 DEG. 41.75' SET NAIL/TAG N/S 8" ASH

303 DEG. 36.10' SET NAIL/TAG N/S 8" ASH

270 DEG. 10.23' FOUND 1/2" IRON ROD AT WEST EDGE OF GRAVEL ROAD

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY
PEER GROUP ON 10-13-00, CO. REP JED

Signed by

Surveyor's Michigan License No.

19834

Date

October 31, 2000