

# SURVEY & REMONUMENTATION

FEB 26 2001

FILED

SECTION

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

2000 NOV -8 A 9:42

NANCY HAVILAND  
REGISTER OF DEEDS  
LIVINGSTON COUNTY, MI.  
48843

LIVINGSTON Located In: Corner Code #  
(County)

1. Public Land Survey T 2 N R 4 E E-07  
T R  
T R  
T R

2. Property Controlling S T R  
in Section S T R

3. Miscellaneous S T R  
Property in Sec. S T R

LSC #1345m

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, JACK K SMITH, in a field survey on AUGUST 4, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

1	A	B	C	D	E	F	G	H	I	J	K	L
2		6		5		4		3		2		1
3												
4		7		8		9		10		11		12
5												
6		18		17		16		15		14		13
7												
8		19		20		21		22		23		24
9												
10		30		29		28		27		26		25
11												
12		31		32		33		34		35		36
13												

A. Description of original monument and accessories and/or subsequent restoration:

GLO 1825 SIBLEY SET POST  
WHITE OAK 12" S 29° W 3.96'  
WHITE OAK 28" N 40° E 31.02'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

THE EXISTING CORNER IS A 1/2" REROD ON THE EAST SIDE OF A WOODEN FENCE POST. THE CORNER LIES 660' NORTHERLY OF LOVE CREEK DRIVE (PRIVATE) ON THE WEST SIDE OF A RESIDENTIAL DRIVEWAY. THERE ARE TREE AND FENCE LINES TO THE NORTH, SOUTH EAST AND WEST.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:


E-07 NORTHWEST CORNER SECTION 21, T2N, R4E, MARION TOWNSHIP, LIVINGSTON COUNTY, MICHIGAN:  
RESET 1/2" REROD WITH 1 1/4" X 36" STEEL PIPE WITH LIVINGSTON COUNTY REMONUMENTATION BRASS CAP WITH SURVEYOR #35999.

N40°E SOUTHWEST CORNER OF HOUSE 259.55'  
NORTH SPIKE AND LIVINGSTON COUNTY REMON TAG IN NORTH SIDE OF A 8" WOOD POST 19.44'  
WEST SPIKE AND LIVINGSTON COUNTY REMON TAG IN NORTH SIDE OF A 8" WOOD POST 0.55'  
S70°E CENTER OF MIDDLE BOLT @ NORTHWEST CORNER OF UTILITY TOWER BASE 21.42'

Signed by

Date

Surveyor's Michigan License No. 35999



FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1975 REVISED JAN. 1983

REVISED OCT., 1995

PA. 345 1999, APPROVED BY LIVINGSTON COUNTY  
PEER GROUP ON 7-19-2000 CO. REP JED