

SURVEY & REMONUMENTATION

FEB 26 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

FILED

For corners in
LIVINGSTON

(County)

Located in: GENOA

Corner Code #

9

2000 NOV 29 A 9:50

NANCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI.
48843

LSC #1385m

Register of Deeds Stamp and File Number

1. Public Land Survey T 2N R 5E C-8
T _____ R _____
T _____ R _____
T _____ R _____
2. Property Controlling S _____ T _____ R _____
in Section S _____ T _____ R _____
3. Miscellaneous S _____ T _____ R _____
Property in Sec. S _____ T _____ R _____
4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Bryan L. Boss, in a field survey on MARCH 2, 2000, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefor as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below.

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1823 BY S. SIBLEY, DEPUTY SURVEYOR
SET POST
B. OAK 26" S 45° E .99 CHAINS
W. OAK 12" N 21° E 1.02 CHAINS

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:


FOUND BOSS CAPPED IRON AT EXTENDED CENTERLINE
WESTPHAL RD

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SET 1 1/4" X 36" PIPE AND BRASS CAP STAMPED
"LIVINGSTON-COUNTY REMONUMENTATION
CORNER"
EAST 38.52' SET REMON NAIL/TAG S/SIDE 8"
CHERRY
SOUTH 4.34' SET REMON NAIL/TAG W/SIDE 14"
OAK
S 5° W 14.25' SET REMON NAIL/TAG W/SIDE 16"
OAK
S 45° W 18.76' SET REMON NAIL/TAG S/SIDE 8"
ASH

N 10° W 23.78' SET REMON NAIL/TAG E/SIDE 40"
OAK

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY
PEER GROUP ON 3-1-2000, CO. REP JED



Signed by

[Signature]

Date

Sept. 5, 2000

Surveyor's Michigan License No.

29238