## **SURVEY &** REMONUMENTATION

FEB 26 2001

**SECTION** 

FILL
------

LAND	CORNER	RECORDATI	ON CEI	RTIF	CATE
illina t	Poguiromo	nt of Act 74	Million	DΛ	1070

2000 NOV 29 A 9:50

	corners in	÷				: <b>a</b>												
LIVINGSTON Loca (County)			cated in:	GENOA	Corner Code #	orner Code #			NANCY HAVILAND REGISTER OF DEEDS									
١.	Public Land Survey	T 2N R 5E E-7					LIVINGSTON COUNTY, MI. 48843											
				_ R _ R														
					,													
2.	Property Controlling	S	_T	_ R						L	SC	#1	138	7m				
	in Section	· S	_T	., R		ľ												
3.	Miscellaneous	S	_ T	_ R		Registe	r of	Dec	eds -	Stam	ıp a	nd 1	File	Nur	nbe	r		
	Property in Sec.	s	_T	_R							<u>.                                    </u>							
4.	Lot No ,	Recorded Pl	at		<del></del>		٠.,											
								A B	С	D	Ę	F (	<u> </u>	1 1	Ţ	Ķ	L	
							ا ً	[	$\perp$	_ <u> </u> _		<u> </u>		$\perp$	_ <u> </u>		ا - ا -	
							3		$\Box$			Ì		$\coprod$	Ĺ		ì	
	Bryan L. Boss				April 14, 2000	•	ار			Ţ							]	
					P.A. of 1970, the corner po	inte mentioned	*	,	$\top$	-i -	Τ,	ו <sup>*</sup>	Γï	Τ	-'i'	$\top$		
		•			ns and rules therefor as re		ъ	$\Box$		$\top$	1				$\neg$	$\neg$	T	
cur	rent manual of survey in	nstructions of	f the Unit	ted States	Department of the Interior, B	Sureau of Land	6	18 1	$\top$	-17	۲'	16 <del>-</del>	- 1º	<u>'</u>	14 I	$\exists$	-13 	
	-				corner points mentioned in	•		一十	_	_	₽	<del>                                     </del>	П	$\dashv$	_	_	十	
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as					8	19	+	-20-	┿2	iı —	-27	2-+	-23	+	-24			
	oressed below.	, re-establish	iea, mon	umentea,	re-monumented, recovered	i, tound as	9	-	-		╁	+-	$\vdash$	$\dashv$	-+	+	╁	
•	NOTE: Not more than 4 corners, all in the same town and range, may be recorded				10	-30	+	-29-	┼;	28 —	2	7+	— <b>2</b> e	+	- 25			
	on this certificate		III (IIC SQI	ii <del>a</del> town t	ina range, may be record	eu.	11			-	╀		⊢	$\dashv$	+	+	+	
							12	ا —31	+	-32-	╁-;	33 —	<u></u> - ⅓	4-	35	-	- 36 1	
Α.	Description of origina	i monument	and acc	essories a	nd/or subsequent restorat	ion:	13	Ш			<u> </u>	<u> </u>	Ш					
	1823 by S. Sibley SET POST				····													

B. OAK 6" N86°W 26 LINKS B. OAK 7" S 32 1/2°E 45 LINKS

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: FOUND 1/2" IRON ROD AT THE INTERSECTION OF CROOKED LAKE AND NIXON ROAD

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner;

SET 1 1/4"X30" PIPE WITH A 1 1/4" X6" PIPE AND BREAKOFF WITH A BRASS CAP STAMPED "LIVINGSTON COUNTY REMONUMENTATION CORNER" N25°E 151.51' SET REMON NAIL TAG W/S 54" OAK N25°E 4.32' FOUND 1/2 IRON ROD N45°E 50.93' FOUND BOSS IRON \$45°E 52.04' NE CORNER 4.8' X 1.8' TEL PEDESTAL

\$45°W 40.31' SET REMON NAIL/TAG W/SIDE 36" OAK N45°W FD CAPPED IRON #12024 48.001

> P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY PEER GROUP ON 4-5-2000 CO. REP JED

> > The state of the s

BRYAN L BOSS and Surveyor

NO.

29238

29238

Surveyor's Michigan License No.