SURVEY & REMONUMENTATION

FEB 26 2001

CECTION

-	-

SEU11	-	A RECORDATION CE									
E to	Filing Requirem	ent of Act 74, Mich.	. P.A. 1970	7	nna i	ini r	· ·				
For corners in LIVINGSTON			19	L	י טטט	AUA 7	29 /	7 0	‡ 5	0	
(County)	Located in: GENOA	Corner Code #	1		NΔ	NCY	HAVIL	A LIS	n		
(County) .					TE U	1311	s ue u	IFFO	re –		
 Public Land Survey 	T 2N R 5E	E-8		L	IVIN(15 I UI	i COUI 843	ŧΪŸ,	MI.		
	T R					440	043				
	TR										
			Y .								
2. Property Controlling in Section	STR		- 1			LS	C #1	388	lm		
	STR										
3. Miscellaneous	STR	***************************************	- Register	of D	eeds	Stam	p and	File	Nur	nber	r
Property in Sec.	s r n	and delices make the contract of the contract				· ··					
4. Lot No	, Recorded Plat		anno menan mananan at a me								
				Α	в с	D (F	G I	<u>H </u>	<u>.</u>	κι
					ļШ	_	!	L		_	!
				3	١	Ů.		Lľ			نــــــــــــــــــــــــــــــــــــــ
Bryan L. Boss	_ , In a field survey on	FEBRUARY 25, 2000		_ له	ļШ	_		L.!	\perp	_ !	!
	requirements of P.A. 74, Michigan P.			,	ÍΙ	Ů.		تــــــــــــــــــــــــــــــــــــــ	\Box	Ï.	نــــــــــــــــــــــــــــــــــــــ
	ere in conformance with regulations			6 -1							
	instructions of the United States De			- '	۱T	-17	16	Γï	ľT	14 	וד
•	of a Court of Law and/or that the come with the rules of the Michigan Boa			7				П		\top	
	d, re-established, monumented, re			8 -1	۱T	- 20 -	7-21 -	Τi	îТ	-23 -	7
expressed below.				*	\Box	1		\sqcap	\sqcap	7	\top
NOTE: Not more than 4 corners, all in the same town and range, may be recorded		ea	1	"	- 29 	—28 —	Τi	7	- 26 ·	7-1	
on this certificat	ie.			1	1-1			\sqcap		1	\top
				12 -:	ïT	32 	—33 —	† 3	1	35	7
A. Description of origina	al monument and accessories and	/or subsequent restorat	tion:		!						
1823 BY S. SIBLEY, DE	EPUTY SURVEYOR										
SET POST W. OAK 30" S 21 1/2* E	E 38 LINKS										
W. OAK 10" N 21 1/2" E											
-	•										

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 1/2" REROD GRAVEL +/- 3' WEST OF CENTERLINE NIXON RD ABOUT 0,25' BELOW **GRAVEL**

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SET 1 1/4" X 36" STEEL PIPE WITH 6" BREAKAWAY PIPE AND A BRASS CAP STAMPED "LIVINGSTON COUNTY REMONUMENTATION CORNER". N 85° E 39.76' SET REMON NAIL/TAG S/SIDE 10" OAK EAST 33.40' FD 1/2" IRON S 15" E 108.66' SET REMON NAIL/TAG W/SIDE 30" OAK S 15° W 98.22' SET REMON NAIL/TAG E/SIDE

TRIPLE OAK

WEST 33.14' FOUND 1/2" PIPE \$ 75' W 31.57' SET REMON NAIL/TAG S/SIDE 14" OSAGE ORANGE

_ Date __

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY PEER GROUP ON 2.2.2000 , CO. REP JED

and Military OF MICHIG BRYAN L BOSS nd Survey NO. 29238 LAND

Signed by	1/ Ben
S	29238