

1993

COMMISSION

For corners in

Property in Sec.

4. Lot No. _ 5. Private Claims __

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

DEC 28 4 17 PM 93

NANCY HAVILAND REGISTER OF DEEDS LIVINGSTON COUNTY, MI 48843

	Livingston	_ Located In:	Corner Code ##
1.	Public Land Survey	T <u>2N</u> R 6E T R R T R R	M-11
2.	Property Controlling in Section	S T R S T R	
3.	Miscellaneous Property in Sec.	S T R S T R	

___ , Recorded Plat __

L.S.C. #137m Register of Deeds Stamp & File Number

I, Bryan Boss , in a field survey on	December 20 , 19 93,							
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned								
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the								
current manual of survey instructions of the United States Department of the Interior, Bureau of Land								
Management or by a decree of a Court of Law and/or that I	the corner points mentioned in lines 3, 4 and 5							
above were in conformance with the rules of the Michigan	in Board of Land Surveyors or by a Decree of a							

expressed below: NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

Court of Law; established, re-established, monumented, re-monumented, recovered, found as

	Α	В	C	Ð	E	F	G	н	l J	K	L	М
2	_	6	-	ļ 5—	L.	4 —		3—		Ĭ	_	
3	L	╙	<u> </u>	<u> </u>	_		_					Ц
4	L	7—	L] B	L.,	9	1	0	_,	1	1	2
5	L			<u> </u>	<u> </u>	<u> </u>						
6		 18	1	7	11	 6	1	5—	_1	4		3
7							<u> </u>					
8		19		0	L_2	1—	L_2	[2	3—	2	4
9	L		ļ.	_				<u> </u>				
10	Ļ	 30	L ₂	9	2	8	2	 :7	2	6	2	5
11	L	_	_			<u> </u>	<u> </u>	\sqcup			Щ	
12	L.	 31	<u> </u> _3	2	3	3	_3	 4	3	5	3	6
12		Ī		I	1	ĺ	`	ı		Ī	Ĭ	

A. Description of original monument and accessories and/or subsequent restoration:

3/4" Iron Pipe Survey Recorded in L. 957, Pg. 346, Livingston Co. Records

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 3/4" Pipe Centerline Labadie Road Fence Line to West

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Reset with 1 1/4" x 36" Breakaway Iron Pipe with Livingston Co. Brass Cap on Top.

N45°W 39.06' Spike S/Side 15" Walnut N50°E 29.06' Spike NW/Side 18" Hickory

S85°E 64.60 Spike S/Side 12" Elm S30°W 31.49' Spike E/Side 12" Hickory N45°E 31.17' Spike W/Side 18" OF M/O

29238

Approved by Livingston Co. Monumentation Peer Group on September 15, 1993

STATE OF MICHIGA BRYAN L. BOSS

and Survey Date NO.

ecember 28, 1993

Surveyor's Michigan License No.

CARREL CONTRACTOR 29238

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971 REVISED MAY 14, 1975

REVISED JAN., 1983