SURVEY & REMONUMENTATION

FEB 2 6 2001

FILED

ates at the	400, 1610	
~ ~ _	, · · ·	Ю'n
375		11.71

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

2000 OCT 19 LA IO: 31

For corners in			i			, , , ,	J .	,		
LIVINGSTON	Located in: BRIGHTON Corner Code #			NAN	ICY HA	VILAN	D			
(County)				REGI	STER O	FDEE	DS			
1. Public Land Survey	T_2N R_6E	T 2N R 6E D-7			STON C 4884		i. m.			
·	TR									
	T R									
	T R									
2. Property Controlling	S TR					-				
in Section	S T R	·	q/	LSC #	1297	n				
3. Miscellaneous	S T R S T R		Registe	r of Deed	is Stam	p and	File N	lumbe	er	
Property in Sec.	S									
4. Lot No.	, Recorded Plat									
				A B	СВ	E F	G H	14	Ķι	لب
					1 1					<u> </u>
				2 J 6 -	_i_	Ti-	Τi	Τî		Ĺ
. Rryan i Ross	M. M.	ARCH 16, 2000		3			\prod	T		Γ
	, in a field survey onM or requirements of P.A. 74, Michigan P.A			. * 7-	11		T'?'	Τï	T	12-
	vere in conformance with regulations a			*			 	\top		T
	instructions of the United States Department		•	8 - 18 -	- - 7-	16°	15	11	'- -	13 ·
	e of a Court of Law and/or that the cor				┪	1-1-	++		\neg	t
	ice with the rules of the Michigan Board			1 8 - 19-	20	21-	-22	+ 2 ² 3	3 -	24
court of Law; established	ed, re-established, monumented, re-n	nonumented, recovered,	, tound as	9		+	+-+-		\dashv	╁
•	4			10 - 30-		I -28-	1 27		₅ - -	1 25
NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.		11	+	- -	++	\dashv		╄		
				12 -31-	<u> </u>	 33-	— 34	—— ar	5	36
A Description of prior	nal monument and accessories and/o	v aubaaguant raatarati	lant	13	تــــــــــــــــــــــــــــــــــــــ	Lï	<u> </u>	تــــــــــــــــــــــــــــــــــــــ	`	ľ
, ,		n sunsequent testorati	ion:							
1823 BY S. SIBLEY, I	DEPUTY SURVEYOR									

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: FOUND 1/2" IRON IN CONCRETE MONUMENT IN OLD FENCE LINE

RUNNING NORTH/SOUTH

W. OAK 8" S 44 1/2" E 48 LINKS W. OAK 6" S 39 1/2 E 33 LINKS

C. Description-of monument for corner and accessories established to perpetuate locating the position of the corner:

SET MONUMENT BRASS CAP STAMPED "LIVINGSTON COUNTY REMONUMENTATION CORNER" NORTH 6.68' SET REMON NAIL/TAG W/SIDE 5" OAK EAST 24.94' SET REMON NAIL/TAG N/SIDE 20" OAK S 10* 3.45' SET REMON NAIL/TAG W/SIDE 18" OAK WEST 23.04' SET REMON NAIL/TAG S/SIDE 20" OAK

> P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY PEER GROUP ON 3-15-2000 CO. REP

Signed by 29238 Surveyor's Michigan License No.

Date

OF MICHIGA

BRYAN L 8088 and Surveyor

NO.

29238

ED LAND SUP