

SURVEY & REMONUMENTATION

FEB 26 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

LIVINGSTON Located In: Corner Code #
(County)
1. Public Land Survey T3N R5E C-10
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

FILED

2000 AUG 29 A 9:30

NANCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI.
48843

LSC #1256m

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, CHARLES E. GARLOCK, in a field survey on JULY 10, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A	B	C	D	E	F	G	H	I	J	K	L	M
1												
2	6		5		4		3		2		1	
3												
4	7		8		9		10		11		12	
5												
6	18		17		16		15		14		13	
7												
8	19		20		21		22		23		24	
9												
10	30		29		28		27		26		25	
11												
12	31		32		33		34		35		36	
13												

A. Description of original monument and accessories and/or subsequent restoration:

GLO 1823 S. SIBLEY SET POST
WHITE OAK 10" N 2 1/2° E 8.58'
WHITE OAK 8" N 77 1/2° E 13.86'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 1/2" IRON ROD APPROXIMATELY 3.5' SOUTH OF THE CENTERLINE OF A 48" OAK IN LINE WITH THE REMAINS OF A FENCE TO THE NORTH AND A NEWER FENCE TO THE EAST AND WEST.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-10 WEST 1/4 CORNER SECTION 29, T3N, R5E, OCEOLA TOWNSHIP, LIVINGSTON COUNTY, MICHIGAN:
SET 1 1/4" X 36" STEEL PIPE WITH LIVINGSTON COUNTY REMONUMENTATION BRASS CAP STAMPED WITH SURVEYOR #14762 IN PLACE OF THE 1/2" IRON ROD.

N15°E SP&TAG E/S 15" HICKORY
N85°E SP&TAG S/S 24" OAK
S45°E SP&TAG N/S 6" ELM
SOUTH SP&TAG E/S 6" ELM

13.52'
38.00'
26.51'
21.43'


Signed by

Charles E. Garlock

Date

7-21-00

Surveyor's Michigan License No. 14762



FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971

REVISED MAY 14, 1975

REVISED JAN, 1983
REVISED OCT, 1995

PA. 345 1990, APPROVED BY LIVINGSTON COUNTY
PEER GROUP ON 3-1-2000 CO. REP JED