

SURVEY & REMONUMENTATION

FEB 26 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

FILED

For corners in

LIVINGSTON Located In: Corner Code #
(County)
1. Public Land Survey T3N R5E D-11
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

2000 AUG 29 A 9:30

NANCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI.
48843

LSC #1260m
Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, CHARLES E. GARLOCK, in a field survey on JULY 10, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L
1												
2		6		5			4		3		2	1
3												
4		7		8			9		10		11	12
5												
6		18		17			16		15		14	13
7												
8		19		20			21		22		23	24
9												
10		30		29			28		27		26	25
11												
12		31		32			33		34		35	36
13												

A. Description of original monument and accessories and/or subsequent restoration:

GLO 1823 S. SIBLEY SET POST
WHITE OAK 14" N48°W 7.92'
WHITE OAK 14" S11 1/2°E 8.58'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 1/2" IRON ROD IN LINE WITH THE REMAINS OF A FENCE TO THE NORTH AND OCCUPATIONS TO THE EAST AND WEST. THE CORNER IS APPROXIMATELY 144' WEST OF THE GENTRY ROAD EXTENSION.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:


D-11 SOUTH 1/4 CORNER SECTION 29, T3N, R5E, OCEOLA TOWNSHIP, LIVINGSTON COUNTY, MICHIGAN:
SET 1 1/4" X 36" STEEL PIPE WITH LIVINGSTON COUNTY REMONUMENTATION BRASS CAP STAMPED WITH SURVEYOR #14762 IN PLACE OF THE 1/2" IRON ROD.

N75°E SP&TAG S/S 16" OAK
S45°E SP&TAG E/S 15" HICKORY
S65°W SP&TAG N/S 12" OAK
N70°W SP&TAG S/S 18" OAK

18.22'
10.38'
21.86'
25.30'

Signed by Charles E. Garlock Date 7-21-00

Surveyor's Michigan License No. 14762



PA. 345 1990, APPROVED BY LIVINGSTON COUNTY
PEER GROUP ON 3-1-2000 CO. REP JED

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1
REVISED MAY 14, 1975 REVISED JAN, 1983
REVISED OCT., 1995