SURVEY & REMONUMENTATION

FEB 2 6 2001

LAND CORNER RECORDATION CERTIFIE	CATE FILED
SECTION Filing Requirement of Act 74, Mich. P.A.	
For corners in	ZAMA AUG 201 A G 21
LIVINGSTON Located In: Corner Code #	2000 AUG 291A 931
1. Public Land Survey T3N R5E E-09	NANCY HAVILAND REGISTER OF DEEDS
TR	LIVINGSTON COUNTY, MI.
2. Property Controlling S T R	
2. Property Controlling S T R	ė
3. Miscellaneous S T R Property in Sec. S T R	LSC #1263m
110puty in 500.	Register of Deeds Stamp & File Number
4. Lot No, Recorded Plat	
5. Private Claims	A B C D E F G H I J K L M
	2 - 6 - 5 - 4 - 3 - 2 - 1
I . CHARLES E. GARLOCK, in a field survey on JULY 10, 2000 do hereby state that under requirement	3 7 8 9 10 11 12
of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with	h 5
regulations and rules therefore as required in the current manual of survey instructions of the United State Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the comment	er 6 18 17 16 15 14 13 13 15 16 17 17 16 17 17 17 18 18 18 18 18 18 18 18 18 18 18 18 18
points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Lan Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expresse	:d
below:	9 - 20 - 21 - 22 - 23 - 24 - 9
NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.	10 30 29 28 27 26 25
on and certificate.	11
	12 31 32 33 34 35 36
	13
A. Description of original monument and accessories and/or subsequent restoration:	
GLO 1823 S. SIBLEY SET POST WHITE OAK 16" SOUTH 25.74'	
WHITE OAK 10" N 29° E 34.32'	
B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:	
FOUND 1/2" IRON ROD IN A MONUMENT BOX IN CENTER OF LATSON ROAD A HIGHLAND ROAD TO THE EAST. THE CENTERLINE OF M-59 IS 151' SOUTH.	IND BIGELOW WEST AND THE REMAINS OF
•	
C. Description of monument for comer and accessories established to perpetuate locating the position of the com-	·
E-09 NORTHEAST CORNER SECTION 29, T3N, R5E, OCEOLA TOWNSHIP, LIVING	STON COUNTY, MICHIGAN:
SET 1 1/4" X 36" BREAKAWAY STEEL PIPE WITH LIVINGSTON COUNTY REMON SURVEYOR #14762 IN PLACE OF THE 1/2" IRON IN THE MONUMENT BOX.	NUMENTATION BRASS CAP STAMPED WITH
N70°W SP&TAG S/S 36" OAK N80°W SP&TAG S/S 40" OAK	81.49' 157.70'
N70°E SP&TAG S/S 32" OAK	85.54' 3E 0 1 1 CHIQ
S85°E SP&TAG N/S 10" PIGNUT HICKORY NORTH 3' +/- CENTERLINE OF BIGELOW ROAD	74.72' & CHARLES E. *
NORTH 8' +/- CENTERLINE OF OLD ROAD EAST	# GARLOCK ** PROFESSIONAL O
1 / 1 / 1)	SURVEYOR S
Simular Market to Int	14762
Signed by Whytho Date Date	POFESSION
Surveyor's Michigan License No. 14762	