

SURVEY & REMONUMENTATION

FEB 26 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

FILED

For corners in

LIVINGSTON Located In: Corner Code #
(County)
1. Public Land Survey T3N R6E H-03
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

2000 AUG 29 A 9 29

NANCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI.
48843

LSC #1246m

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, CHARLES E. GARLOCK, in a field survey on JULY 11, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6			5			4		3		2		1
3													
4	7			8			9		10		11		12
5													
6	18			17			16		15		14		13
7													
8	19			20			21		22		23		24
9													
10	30			29			28		27		26		25
11													
12	31			32			33		34		35		36
13													

A. Description of original monument and accessories and/or subsequent restoration:

GLO 1823 S. SIBLEY SET POST
HICKORY 10" N79°W 27.72'
WHITE OAK 8" N49°E 4.62'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:


WE FOUND A 1/2" IRON ROD IN LINE WITH THE REMAINS OF AN OLD FENCE TO THE NORTH AND 4' WEST OF A NEWER FENCE TO THE NORTH. IT IS ALSO 2' WEST OF A FENCE TO THE SOUTH. THE FOUND IRON IS 3' NORTH OF THE ROAD CENTERLINE.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H-03 SOUTH 1/4 CORNER SECTION 3, T3N, R6E, HARTLAND TOWNSHIP, LIVINGSTON COUNTY, MICHIGAN:
SET 1 1/4" X 36" BREAKAWAY STEEL PIPE WITH LIVINGSTON COUNTY REMONUMENTATION BRASS CAP STAMPED WITH SURVEYOR #14762 IN THE PLACE OF THE FOUND 1/2" IRON ROD.

SOUTH SP&TAG W/S 12" HICKORY
S70°W SP&TAG N/S 18" OAK
N15°W SP&TAG W/S 13" OAK
N45°E SP&TAG S/S 48" OAK
SOUTH 2' +/- CENTERLINE OF CLYDE ROAD

38.09'
96.45'
31.99'
42.95'



Signed by Charles E. Garlock

Date 7-21-00

Surveyor's Michigan License No. 14762