SURVEY & REMONUMENTATION

FEB 26 2001

FILED

SECTION

Signed by Surveyor's Michigan License No. 39096

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970, 001 001 30 1 \triangle 9: 22

For corners in			NANCY HAVILAND REGISTER OF DEEDS LIVINGSTON COUNTY, MI.						
Livings (County			Gare (Irse	4887					
1. Public Land Survey T <u>4N R4E L-5</u> T R T R			LSC #1334m Register of Deeds Stamp & File Number						
in Se 3. Misc	erty Controlling S		А В	C D	E F	э н	ı j k	L M	
4. Lot N	io, Recorded Plat	_ 2	6	5	4	3	2	1	
i,	John H. Rauser, P.S. , in a field survey on July 10 2000	— 3 4	7	8	9	10	11	12	
do hereb in lines	y certify that under requirements of P.A. 74, Michigan P.A. of 1970, the comer points m I and 2 above were in conformance with regulations and rules therefore as require	ed in the 6	18	17	16	15	14	13	
Managen above w	nanual of survey instructions of the United States Department of the Interior, Bureau lent or by a decree of a Court of Law and/or that the corner points mentioned in lines 3 ere in conformance with the rules of the Michigan Board of Land Surveyors or by a De Law; established, re-established, monumented, re-monumented, recovered, f	4 and 5 cree of a 8	19	20	21	22	23	24	
expresse	d below:	10	30	29	28	27	26	25	
NOTE:	Not more than 4 corners, all in the same town and range, may be recorded on this certificate.	ed 11 12 13	31	32	33	34	35	36	
<u>L-5</u>	common 1/4 Corner, Sections 12 & 13, T4N-R4E, Cohoctah Township, Living 1823 Wood post placed by Sylvester Sibley, Deputy Surveyor, two willinks 18" W. Oak and S53E 27 links 16" W. Oak. (Continued on Back) common 1/4 Corner evidence found and/or method applied in rest Common 1/4 Corner, Sections 12 & 13, T4N-R4E, Cohoctah Township, Living Found no evidence of original government corner. Found 3" iron pipe fence lines running North-South and East-West, and on the North sid found pipe with witnesses and measurements from 1971 to present this position. We recommend that the found iron pipe be accepted as original government corner and a standard Livingston County brass of GPS.	coring or aston Cour in concrete of old to Found not the best	reesta tty ete at t vo-trac conflic availal	marke blishin he bas k. Veri bling evole evid	e of a lified the	er: flat met e positi e in the of the p	al post on of the vicinity	, on ne of the	
C. D corner	escription of monument for corner and accessories established to: : Common 1/4 Comer, Sections 12 & 13, T4N-R4E, Cohoctah Township, Livin			eating	the po	sition	of the		
_	Set standard Livingston County brass cap stamped "L-5 39096" in c			ng 3" p	ipe.				
	East 1.30' Set Carsonite Survey Marker post South 13.80' Set nail with Livingston County Survey Witness Tag N80W 45.82' Set nail with Livingston County Survey Witness Tag N60E 21.40' Set nail with Livingston County Survey Witness Tag Set nail with Livingston County Survey Witness Tag	in West fa	ice of v	vood fe	ence po	ost herry			

PA. 345 1990, APPROVED BY LIVINGSTON COUNTY
PEER GROUP ON 6 2/2020 CO. REP UED.

FORM APPROVED BY

AF LAND SUBVETONS, JAN. 21, 19 AT EVENTED MAY 14, 19 EVISED JAN., 19 R WORD PROSESSING MARCH, 19