

LIVINGSTON

# LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF --:	LOCATED IN --:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY <u>19</u> T. <u>4</u> N. R. <u>5</u> E. <u>13</u>		A-7, A-8
2. PROPERTY CONTROLLING IN SECTION _____, T. _____ N. S., R. _____ E. W.		
3. MISCELLANEOUS PROPERTY IN SECTION _____, T. _____ N. S., R. _____ E. W.		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Donald Bissell, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on November, 19 81, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_, 19 \_\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

A-7 Found fences going N-S and E. Set 4"x 36" concrete monument with aluminum cap at inter. Distances check G.L.O. to the South reasonably close.

A-8 Set 4"x 36" concrete monument with aluminum cap. Set midway and on line.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-7 4"x 36" concrete monument with aluminum cap  
 S 23° W, 10.67', 16" R. Oak, Spike and Tag  
 S 72° W, 37.77', 5" Maple, Spike and Tag  
 N 50° E, 46.51', 22" R. Oak, Spike and Tag  
 S 40° E, 8.74', 7" R. Oak, Spike and Tag  
 South, 22.44', Concrete Monument  
 South, 87', North edge Hidden Lake  
 All trees blazed

A-8 4"x 36" concrete monument with aluminum cap.  
 N 46° W, 22.77', 12" Cherry, Spike & Tag  
 S 30° W, 10.02', 16" W. Oak, Spike & Tag  
 S 47° E, 17.00', 20" W. Oak, Spike & Tag  
 N 86° E, 20.85', 22" W. Oak, Spike & Tag  
 North, 8', E-W fence line

SIGNED BY Donald Bissell DATE 12-24-81

SURVEYOR'S MICHIGAN REGISTRATION NO. 18655

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
 CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
 MICHIGAN REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_