

MAR 17 2000

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

FILED

For corners in

LIVINGSTON
(County)

Located in:

Corner Code #

1. Public Land Survey

T 4N R 5E I-09

2. Property Controlling
in Section

S T R

3. Miscellaneous
Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

1999 NOV 22 A 10:08

NANCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI.
48843

JSC# 1093m

Register of Deeds Stamp & File
Number

I, **MARY A. BARNWELL**, in a field survey on **SEPTEMBER 29, 1999** do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

I-09 Deerfield Township was set by the GLO in 1823.

The original witnesses are:

Stream 8 West South 1.35 (89.1')

Poplar 14" S. 00° 30' W. 3.43 (226.4')

White Oak 14" N. 03°W. 7.30 (481.8')

NOTE: None of the original witnesses could be found or perpetuated.
See the back of this sheet for additional historical data.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I-09 Found - 1 1/2" diameter Iron Pipe 2 feet below grade in a cultivated field 60 feet West of the centerline intersection of Argentine Road (asphalt surface running North/South) and Dean Road (gravel surface running East). Set by Darrell D. Hughes, PS #19834 in 1992 by double proportionate measurement from field notes by M. W. Bullock, Deputy County Surveyor, dated July 1870 (see historical data) which he adjusted 1.62 feet North to fall on a line from the South 1/4 corner of Section 23 extended West through a found railroad spike at the centerline of Argentine Road.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-09 Southwest Corner, Section 23, T4N, R5E - Reset 1 1/2" Iron Pipe with 36" x 1 1/4" break-off pipe with Brass Cap marked as "Livingston County Monumentation Corner" 2' below surface at East edge of plowed field and 60 feet West of the centerline intersection of Argentine and Dean Roads.

East Found RR Spike at Grade with Asphalt Centerline of Argentine and Dean Roads

S 53° W Set Nail/Remon Washer NW/S Triple 6" Elm 75.34'

S 69° E Set Nail/Remon Washer W/S 16" Cottonwood 114.63'

East Orange Fiberglass Carsonite Survey Marker 4 foot high 16.75'

N 73° E Set Nail/Remon Washer S/S 12" Cottonwood 33.87'

N 37° E Set Nail/Remon Washer SE/S 14" Cotton Wood 54.03'

Signed by

Date

Surveyor's Michigan License No. 33971

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY

PEER GROUP ON 9-15-99 CO. REP JED

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983
REVISED OCT., 1995

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

