

Filing Requirement of Act 74, Mich. P.A. 1970

Mackinac
(County)

Corner Code ~~##~~

T40N R4W

M-1

S _____ T _____ R _____

~~Twp cor common to
Sec.'s 1-6-31-36~~

S _____ T _____ R _____

4. Lot No. _____, Recorded Plat _____

5. Private Claims

I, Neil E. Hill, in a field survey on SEPTEMBER 30, 1996, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G.L.O. notes. Set Township corner.

8" Cedar S08W 16 lks

5" Aspen N49E 19 lks

8" Cedar S26E 22 lks

From survey of Section 36 by C.A.&E. 1977.

3/4" solid iron

Recorded on U.S.F.S. Plat drawing.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found iron in monument box

Township corner. 3/4" steel rod with cap #27464.

PP S68W 45.85'

PP N70W 50.70'

Hydrant N35E 32.65'

Accepted corner location.

SURVEY & REMONUMENTATION

MAY 20 1997

COMMISSION

ACCEPTED BY THE MACKINAC COUNTY
SURVEY PEER GROUP AS THE
OFFICIAL CORNER UNDER P.A.
345 OF 1990 AT A MEETING
HELD ON 9-30-96

James H. Granger

Also recorded in: T41N, R4W, M-13; T40N, R3W, A-1; T41N, R3W, A-13

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Accepted 3/4" steel rod with cap #27464 in monument box as township corner.

PP S68W 46.00' (side)

PP N70W 50.98' (side)

Hydrant N35E 32.75' (top)

SW corner of concrete garage foundation N15E 76.58'



Signed by Neil E. Abel P.S., P.C.
27447
Surveyor's Michigan License No. _____

SEPTEMBER 30, 1996

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

E 0090