

SURVEY &
REMONUMENTATION

OCT 11 1994

COMMISSION

MACKINAC COUNTY REMONUMENTATION CORNER
LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Mackinac

(County)

Located In:

Corner Code ##

1. Public Land Survey

T 40N R 4W

MC of G-5/H-5

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No.

, Recorded Plat

5. Private Claims

RECEIVED & FILED
DIANE FRANKOVICH
MACKINAC COUNTY CLERK OF DEEDS

SEP 6 1994

AM

PM

7/8/9/10/11/12/13/14/15/16

Register of Deeds Stamp & File Number

Neil E. Hill

August 22

94

I, Neil E. Hill, in a field survey on August 22, 1994, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Set Meander Corner at 78.50 ch. then offset 1.50 ch.

Set post

Tied 4" Fir N43E 0.17 ch

3" Fir N25W 1.0 ch

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Parole evidence indicates that a steel jacket water tank was set at the Section Corner location by Ford Huyck and his father.

This location is indicated on the Josephine Levellie Plat. It has been used as the Section Corner and is located in the Moran River.

1976 Feindt survey to North

1977 Connell MDOT recorded Liber B, page 65.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 5/8" re-rod with 4" aluminum cap 99.00 feet East of steel water tank on E-W Section line.

P.Pole East 03.43'

T.Pole North 09.67'

5" Spruce N55W 17.70'

5" Spruce S70W 55.78'

ACCEPTED BY THE MACKINAC COUNTY
SURVEY PEER GROUP AS THE
OFFICIAL CORNER UNDER P.A.
345 OF 1990 AT A MEETING
HELD ON 8-16-94

James H. Granger

Signed by Neil E. Hill P.S. Date August 22, 1994

Surveyor's Michigan License No. 27447

0-0278

09-06-94 1CL3183

MSSR