OCT 1 1 1994

## COMMISSION MACKINAC COUNTY REMONUMENTATION CORNER LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

Mackinac	
Located In: Corner Code =##	RECEIVED & FILLS
1. Public Land Survey	DIVVIE EBVERCOAICH
TR	
TR	SEP 6 1994 PM
Property Controlling S T B	
. Property Controlling S T R in Section S T R	7/8/9/10/11/12/1/2/3/4/5/6
Miscellaneous S T R	A
Property in Sec. S T R	Register of Deeds Stamp & File Number
Lot No, Recorded Plat	
Private Claims Northwest Corner of Private Claim 17,	ABCDEFGHIJKL
T40N, R04W, Moran Township	2 5 4 3 2
Neil E. Hill August 22 94	3
in a field survey on	
hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned lines 1 and 2 above were in conformance with regulations and rules therefore as required in the property of the corner points.	ed 6 18 17 16 15
interit indition of survey instructions of the United States Department of the Interior Purpose of Land	اللللللللا
anagement or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and over were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of Nurt. of Laws, and other weeks of the Michigan Board of Land Surveyors or by a Decree of	1e
the bir Law, established, re-established, monumented, re-monumented, recovered, found is	fa as 9
pressed below:	10 30 29 28 27 26 2
OTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.	11
on this certificate.	12 31 32 33 34 35 36
Description of original monument and accessories and/or subsequent restoration:	13
et post	
Description of corner evidence found and/or method applied in restoring or reestablish	shing corner:
Description of corner evidence found and/or method applied in restoring or reestablis records of corner indt surveys in the area	shing corner:
Description of corner evidence found and/or method applied in restoring or reestablished to the corner indicated and the corner location.	shing corner:
Description of corner evidence found and/or method applied in restoring or reestablish records of corner indt surveys in the area und 2" pipe at the corner location 7" Firch NOSE 11.20' (gone)	shing corner:
Description of corner evidence found and/or method applied in restoring or reestablish records of corner indt surveys in the area und 2" pipe at the corner location 7" Birch NOSE 11.20' (gone) 3" & 4" Tw Cedar SOSW 22.00'	
Description of corner evidence found and/or method applied in restoring or reestablish records of corner condt surveys in the area and 2" pipe at the corner location 7" Birch NOSE 11.20' (gone) 3" & 4" Tw Cedar SOSW 22.00' STREET SOSW 22.00' STREET SOSW SOSW SOSW SOSW SOSW SOSW SOSW SOS	CCEPTED BY THE MACKINAC COUNTY URVEY PEER GROUP AS THE FFICIAL CORNER UNDER P.A. 15 OF 1990 AT A MEETING
Description of corner evidence found and/or method applied in restoring or reestablish records of corner condt surveys in the area and 2" pipe at the corner location 7" Birch NOSE 11.20' (gone) 3" & 4" Tw Cedar SOSW 22.00' STREET SOSW 22.00' STREET SOSW SOSW SOSW SOSW SOSW SOSW SOSW SOS	CCEPTED BY THE MACKINAC COUNTY URVEY PEER GROUP AS THE FFICIAL CORNER UNDER P.A. 15 OF 1990 AT A MEETING ELDON B-16-94
Description of corner evidence found and/or method applied in restoring or reestablished a corner for the area and 2" pipe at the corner location 7" Firch NOSE 11.20' (gone) 3" & 4" Tw Cedar SOSW 22.00' 8" Beech S75E 22.30' A	CCEPTED BY THE MACKINAC COUNTY URVEY PEER GROUP AS THE FFICIAL CORNER UNDER P.A. 15 OF 1990 AT A MEETING
Description of corner evidence found and/or method applied in restoring or reestablish records of corner indt surveys in the area und 2" pipe at the corner location 7" Birch NØSE 11.20' (gone) 3" & 4" Tw Cedar SØSW 22.00' 8" Beech S75E 22.30' A S	CCEPTED BY THE MACKINAC COUNTY URVEY PEER GROUP AS THE FFICIAL CORNER UNDER P.A. 15 OF 1990 AT A MEETING ELDON B-16-94
Description of corner evidence found and/or method applied in restoring or reestablish records of corner indt surveys in the area und 2" pipe at the corner location 7" Birch NOSE 11.20' (gone) 3" & 4" Tw Cedar SOSW 22.00' 8" Beech S75E 22.30' A SOSW SOSW SOSW SOSW SOSW SOSW SOSW SO	CCEPTED BY THE MACKINAC COUNTY URVEY PEER GROUP AS THE FFICIAL CORNER UNDER P.A. 15 OF 1990 AT A MEETING ELDON B-16-94
Description of corner evidence found and/or method applied in restoring or reestablish records of corner indictions of corner location. The area and 2" pipe at the corner location 7" Birch NBSE 11.20' (gone) 3" & 4" Tw Cedar SOBW 22.00' A SOBW 22.00' STOE 22.30' A SOBW SOBW SOBW SOBW SOBW SOBW SOBW SOBW	CCEPTED BY THE MACKINAC COUNTY URVEY PEER GROUP AS THE FFICIAL CORNER UNDER P.A. 15 OF 1990 AT A MEETING ELDON B-16-94
Description of corner evidence found and/or method applied in restoring or reestablish records of corner rindt surveys in the area and 2" pipe at the corner location 7" Birch NOSE 11.20' (gone) 3" & 4" Tw Cedar SOSW 22.00' A S' Beech S75E 22.30' A B'	CCEPTED BY THE MACKINAC COUNTY URVEY PEER GROUP AS THE FFICIAL CORNER UNDER P.A. 15 OF 1990 AT A MEETING ELDON B-16-94
Description of corner evidence found and/or method applied in restoring or reestablished surveys in the area und 2" pipe at the corner location 7" Firch NBSE 11.20' (gone) 3" & 4" Tw Cedar SOSW 22.00' 8" Beech S75E 22.30'  A O O O O O O O O O O O O O O O O O O	CCEPTED BY THE MACKINAC COUNTY URVEY PEER GROUP AS THE FFICIAL CORNER UNDER P.A. AS OF 1990 AT A MEETING ELDON 8-16-94
Description of corner evidence found and/or method applied in restoring or reestablished corner as found.  Description of corner evidence found and/or method applied in restoring or reestablished to perpetuate location and surveys in the area and surveys (gone)  3" & 4" Tw Cedar S08W 22.00'  Bescription of monument for corner and accessories established to perpetuate location and surveys	CCEPTED BY THE MACKINAC COUNTY URVEY PEER GROUP AS THE FFICIAL CORNER UNDER P.A. 15 OF 1990 AT A MEETING ELDON B-16-94
Description of corner evidence found and/or method applied in restoring or reestablished surveys in the area und 2" pipe at the corner location 7" Birch NOBE 11.20' (gone) 3" & 4" Tw Cedar SOBW 22.00' 8" Beech S75E 22.30' A S O O O O O O O O O O O O O O O O O O	CCEPTED BY THE MACKINAC COUNTY URVEY PEER GROUP AS THE FFICIAL CORNER UNDER P.A. 15 OF 1990 AT A MEETING ELDON B-16-94  THE MICHINAL MICHI
Description of corner evidence found and/or method applied in restoring or reestables records of corner indt surveys in the area and 2" pipe at the corner location 7" Birch NBBE 11.20' (gone) 3" & 4" Tw Cedar SBBW 22.80' 8" Beech S75E 22.30' A  Bescription of monument for corner and accessories established to perpetuate location of the corner as found.  Bescription of monument for corner and accessories established to perpetuate location of the corner as found.  Bescription of monument for corner and accessories established to perpetuate location of the corner as found.  Bescription of monument for corner and accessories established to perpetuate location of the corner as found.  Bescription of monument for corner and accessories established to perpetuate location of the corner as found.  Bescription of monument for corner and accessories established to perpetuate location of the corner as found.  Bescription of monument for corner and accessories established to perpetuate location of the corner as found.  Bescription of monument for corner and accessories established to perpetuate location of the corner as found.  Bescription of monument for corner and accessories established to perpetuate location of the corner as found.	CCEPTED BY THE MACKINAC COUNTY URVEY PEER GROUP AS THE FFICIAL CORNER UNDER P.A. 45 OF 1990 AT A MEETING ELDON B-/6-94  ALLE HILL HELL HILL  HELL HILL  HELL  HILL  HELL  HILL  HELL  HILL  HILL
Description of corner evidence found and/or method applied in restoring or reestables or records of corner exind surveys in the area and 2" pipe at the corner location  7" Birch NOBE 11.20' (gone)  3" & 4" Tw Cedar SOBW 22.00'  8" Beech S75E 22.30'  A  Bescription of monument for corner and accessories established to perpetuate location of the corner as found.  George of the corner as found.  George of the corner and accessories established to perpetuate location of the corner as found.  George of the corner and accessories established to perpetuate location of the corner as found.  George of the corner and accessories established to perpetuate location of the corner as found.  George of the corner and accessories established to perpetuate location of the corner as found.  George of the corner and accessories established to perpetuate location of the corner as found.  George of the corner and accessories established to perpetuate location of the corner and accessories established to perpetuate location of the corner and accessories established to perpetuate location of the corner and accessories established to perpetuate location of the corner and accessories established to perpetuate location of the corner and accessories established to perpetuate location of the corner and accessories established to perpetuate location of the corner and accessories established to perpetuate location of the corner and accessories established to perpetuate location of the corner and accessories established to perpetuate location of the corner and accessories established to perpetuate location of the corner and accessories established to perpetuate location of the corner and accessories established to perpetuate location of the corner and accessories established to perpetuate location of the corner and accessories established to perpetuate location of the corner and accessories established to perpetuate location of the corner and acce	CCEPTED BY THE MACKINAC COUNTY URVEY PEER GROUP AS THE FFICIAL CORNER UNDER P.A. 15 OF 1990 AT A MEETING ELDON B-16-94  The position of the corner:  NET 2  HILL Land Burveyor
Description of corner evidence found and/or method applied in restoring or reestables records of corner indt surveys in the area und 2" pipe at the corner location 7" Birch NBBE 11.28' (gone) 3" & 4" Tw Cedar SBBW 22.00' 8" Beech S75E 22.30' A  O  O  O  O  O  O  O  O  O  O  O  O	CCEPTED BY THE MACKINAC COUNTY URVEY PEER GROUP AS THE FFICIAL CORNER UNDER P.A. 15 OF 1990 AT A MEETING ELDON B-16-94  MEN B-16-94  MEN B-16-94  MILL Land Burveyor No.
Description of corner evidence found and/or method applied in restoring or reestablish records of corner rindt surveys in the area and 2" pipe at the corner location 7" Birch NØSE 11.20' (gone) 3" & 4" Tw Cedar SØSW 22.00' 8" Beech S75E 22.30' AS O 34 HI SECTION OF MONUMENT OF CORNER AND SECTION OF MONUMENT OF CORNER AND SECTION OF TWO CEDAR SØSW 22.00' 8" Beech S75E 22.30' 10" W. Birch NIDE 11.83' 8" Maple NASW 52.51' 10" Birch NASW 36.24' Monument box NBGE 258.12'	CCEPTED BY THE MACKINAC COUNTY URVEY PEER GROUP AS THE FFICIAL CORNER UNDER P.A. 15 OF 1990 AT A MEETING ELDON 6-16-94  The position of the corner:  MEN 2  HILL  Land  Gurveyor  No.
Description of corner evidence found and/or method applied in restoring or reestablish records of corner rindt surveys in the area and 2" pipe at the corner location 7" Birch N08E 11.20' (gone) 3" & 4" Tw Cedar S08W 22.00' 8" Beech S75E 22.30'  Solution of monument for corner and accessories established to perpetuate locating the state of the solution of the solut	CCEPTED BY THE MACKINAC COUNTY URVEY PEER GROUP AS THE FFICIAL CORNER UNDER P.A. 15 OF 1990 AT A MEETING ELDON 6-16-94  The position of the corner:  MEN 2  HILL  Land  Gurveyor  No.